

Package **deTestSet**: testset for initial value problems of differential equations in R

Karline Soetaert

Royal Netherlands Institute of Sea Research
Yerseke, The Netherlands

Jeff Cash

Dipartimento di Matematica
Imperial College London
U.K.

Francesca Mazzia

Universita' di Bari
Italy

Abstract

R package **deTestSet** contains the R-version of the ODE and DAE initial value problems test set from <http://www.dm.uniba.it/~testset> Mazzia and Magherini (2008).

If the model problem is small enough, then it is implemented in pure R . For larger models, the problem specified in FORTRAN code at the website of Jeff Cash http://www.ma.ic.ac.uk/~jcash/IVP_software were used.

These implementations were compiled as DLLs, and included in the package. The code of these models can be found in the packages `inst/examples/dynload` subdirectory.

For a number of small models, we show how to implement them in R .

Keywords: ordinary differential equations, differential algebraic equations, initial value problems, testset, R.

```
> out <- andrews()

Andrews' squeezing mechanism
Solved with mebdfi
Using rtol = 1e-07, atol=1e-07
Mixed error significant digits:
1.406245

> plot(out, which = 1:9, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "andrews", cex = 1.5)
```




Figure 1: the andrews problem- see text for R-code




Figure 2: Solution of beam - see text for R-code

```

> out <- beam()

Beam
Solved with gamd
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits:
4.98705

> plot(out, which = 1:9, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "beam", cex = 1.5)

```




Figure 3: Solution of caraxis - see text for R-code

```
> out <- caraxis()

Car Axis problem
Solved with mebdfi
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits:
3.331363

> plot(out, which = 1:9, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "caraxis", cex = 1.5)
```




Figure 4: Solution of crank - see text for R-code

```
> out <- crank()

Slider Crank
Solved with mebdfi
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits (first seven components):
8.456184

> plot(out, which = 1:9, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "crank", cex = 1.5)
```




Figure 5: Solution of E5 - see text for R-code

```
> out <- E5()

Problem E5 stiff-detest
Solved with lsoda
Using rtol = 1e-06, atol=1.11e-24
Mixed error significant digits:
-0.332505

> plot(out, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "E5", cex = 1.5)
```




Figure 6: Solution of emep - see text for R-code

```
> out <- emep()

EMEP problem
Solved with bimd
Using rtol = 1e-05, atol=0.1
Mixed error significant digits:
3.57872

> plot(out, which = 1:9, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "emep", cex = 1.5)
```




Figure 7: Solution of fekete - see text for R-code

```
> out <- fekete()

Fekete problem
Solved with mebdfi
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits:
7.580798

> plot(out, which = 1:9, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "fekete", cex = 1.5)
```




Figure 8: Solution of hires - see text for R-code

```
> out <- hires()

Problem HIRES
Solved with mebdfi
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits:
5.567281

> plot(out, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "hires", cex = 1.5)
```




Figure 9: Solution of nand - see text for R-code

The nand problem is most efficiently solved with **daspk**

```
> out <- nand(method = daspk)

NAND gate
Solved with daspk
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits:
5.556794

> plot(out, which = 1:9, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "nand", cex = 1.5)
```




Figure 10: Solution of orego - see text for R-code

```

> out <- orego()

Problem OREGONATOR
Solved with lsoda
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits:
4.768192

> plot(out, lwd = 2, ask = FALSE, log = "y")
> mtext(outer = TRUE, side = 3, line = -1.5, "orego", cex = 1.5)

```




Figure 11: Solution of pollution - see text for R-code

```
> out <- pollution()

Pollution problem
Solved with mebdfi
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits:
6.733499

> plot(out, which = 1:9, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "pollution", cex = 1.5)
```




Figure 12: Solution of ring - see text for R-code

```
> out <- ring()

Ring Modulator
Solved with mebdfi
Using rtol = 1e-08, atol=1e-08
Mixed error significant digits:
6.308331

> plot(out, which = 1:9, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "ring", cex = 1.5)
```




Figure 13: Solution of rober - see text for R-code

```
> out <- rober()

Problem ROBERTSON
Solved with lsoda
Using rtol = 1e-10, atol=1e-14
Mixed error significant digits:
9.304309

> plot(out, lwd = 2, ask = FALSE, log = "x", xlim = c(1e-05,1e11))
> mtext(outer = TRUE, side = 3, line = -1.5, "rober", cex = 1.5)
```




Figure 14: Solution of transistor - see text for R-code

```
> out <- transistor()

Transistor Amplifier
Solved with mebdfi
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits:
6.219765

> plot(out, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "transistor", cex = 1.5)
```




Figure 15: Solution of tube - see text for R-code

```
> out <- tube()

Water tube system
Solved with radau5
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits:
5.482282

> plot(out, which = 1:9, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "tube", cex = 1.5)
```




Figure 16: Solution of twobit - see text for R-code

```

> out <- twobit()

Two bit adding unit
Solved with radau5
Using rtol = 1e-04, atol=1e-04
Mixed error significant digits:
4.924473

> plot(out, which = 1:9, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "twobit", cex = 1.5)

```




Figure 17: Solution of vdpol - see text for R-code

```
> out <- vdpol()

Problem VANDERPOL
Solved with lsoda
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits:
6.051236

> plot(out, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "vdpol", cex = 1.5)
```




Figure 18: Solution of wheelset an implicit differential equation model - index 2, dimension 17 - see text for R-code

```
> out <- wheelset()

Wheelset
Solved with mebdfi
Using rtol = 1e-06, atol=1e-06
Mixed error significant digits:
3.636501

> plot(out, which = 1:6, lwd = 2, ask = FALSE)
> mtext(outer = TRUE, side = 3, line = -1.5, "wheelset", cex = 1.5)
```

References

Mazzia F, Magherini C (2008). *Test Set for Initial Value Problem Solvers, release 2.4.* Department of Mathematics, University of Bari, Italy. Report 4/2008, URL <http://pitagora.dm.uniba.it/~testset>.

Affiliation:

Karline Soetaert
 Royal Netherlands Institute of Sea Research (NIOZ)
 4401 NT Yerseke, Netherlands
 E-mail: karline.soetaert@nioz.nl
 URL: <http://www.nioz.nl>

Jeff Cash
 Imperial College London
 South Kensington Campus
 London SW7 2AZ, U.K.
 E-mail: j.cash@imperial.ac.uk
 URL: <http://www.ma.ic.ac.uk/~jcash>

Francesca Mazzia
 Dipartimento di Matematica
 Universita' di Bari
 Via Orabona 4,
 70125 BARI
 Italy E-mail: mazzia@dm.uniba.it
 URL: <http://pitagora.dm.uniba.it/~mazzia>