

# Package ‘MPCR’

November 22, 2023

**Type** Package

**Title** Multi Precision Computing

**Version** 1.0

**Date** 2023-11-12

**Author** David Helmy [aut, cph], Sameh Abdulah [cre, cph], KAUST King Abdullah University of Science and Technology [fnd, cph], Brightskies [cph]

**Maintainer** Sameh Abdulah <sameh.abdulah@kaust.edu.sa>

**Description** Provides new data-structure support for multi- and mixed-precision for R users. The package supports 16-bit, 32-bit, and 64-bit operations with the ability to perform mixed-precision operations through a newly defined tile-based data structure. To the best of our knowledge, 'MPCR' differs from the currently available packages in the following: 'MPCR' introduces a new data structure that supports three different precisions (16-bit, 32-bit, and 64-bit), allowing for optimized memory allocation based on the desired precision. This feature offers significant advantages in-memory optimization. 'MPCR' extends support to all basic linear algebra methods across different precisions. 'MPCR' maintains a consistent interface with normal R functions, allowing for seamless code integration and a user-friendly experience. 'MPCR' also introduces support for the tile-based matrix data structure with mixed precision, enabling the utilization of a range of tile-based linear algebra algorithms.

**License** GPL (>= 3)

**Imports** methods, Rcpp (>= 1.0.9)

**Depends** R (>= 3.6.0)

**RoxygenNote** 7.2.3

**SystemRequirements** CMake (>=3.20) , C++ (>= 11)

**NeedsCompilation** yes

**OS\_type** unix

**URL** <https://github.com/stsds/MPCR>

**VignetteBuilder** rmarkdown

**Suggests** knitr, rmarkdown, utils

**R topics documented:**

01-MPCR . . . . .	3
02-MPCRTile . . . . .	4
03-Converters . . . . .	6
04-Arithmetic . . . . .	7
05-Comparison . . . . .	8
06-Extract-Replace . . . . .	10
07-Dimensions . . . . .	11
08-Copy . . . . .	11
09-Concatenate . . . . .	12
10-Bind . . . . .	13
11-Diagonal . . . . .	14
12-Extremes . . . . .	14
13-Log . . . . .	15
14-Mathis . . . . .	16
15-Miscmath . . . . .	17
16-NA's . . . . .	17
17-Replicate . . . . .	18
18-Round . . . . .	19
19-Scale . . . . .	20
20-Sweep . . . . .	20
21-Special Math . . . . .	21
22-Trig . . . . .	22
23-Hyperbolic . . . . .	23
24-Transpose . . . . .	24
25-Check precision . . . . .	24
26-Metadata . . . . .	25
27-Print . . . . .	26
28-Cholesky decomposition . . . . .	27
29-Cholesky inverse . . . . .	27
30-Crossprod . . . . .	28
31-Eigen decomposition . . . . .	29
32-Symmetric . . . . .	30
33-Norm . . . . .	31
34-QR decomposition . . . . .	31
35-Reciprocal condition . . . . .	32
36-Solve . . . . .	33
37-Singular value decomposition . . . . .	34
38-Back/Forward solve . . . . .	35
39-MPCR GEMM . . . . .	36
40-MPCR TRSM . . . . .	37
41-MPCRTile GEMM . . . . .	38
42-MPCRTile POTRF . . . . .	39
43-MPCRTile TRSM . . . . .	40

## Description

MPCR is a multi-precision vector/matrix, that enables the creation of vector/matrix with three different precisions (16-bit (half), 32-bit(single), and 64-bit(double)).

## Value

MPCR object (constructor - accessors - methods)

## Constructor

`new` Creates a new instance of zero values of the MPCR class. `new (MPCR, size, "precision")`

`size` The total number of values for which memory needs to be allocated.

`precision` String to indicate the precision of MPCR object ("half", "single", or "double").

## Accessors

The following accessors can be used to get the values of the slots:

`IsMatrix` Boolean to indicate whether the MPCR object is a vector or matrix.

`Size` Total number of elements inside the object, (row\*col) in the case of matrix, and number of elements in the case of vector.

`Row` Number of rows.

`Col` Number of cols.

## Methods

The following methods are available for objects of class MPCR:

**PrintValues:** `PrintValues()`: Prints all the values stored in the matrix or vector, along with metadata about the object.

**ToMatrix:** `ToMatrix(row, col)`: Changes the object representation to match the new dimensions, no memory overhead.

**ToVector:** `ToVector()`: Changes the MPCR matrix to vector, no memory overhead.

## Examples

```
# Example usage of the class and its methods
library(MPCR)
MPCR_object <- new(MPCR, 50, "single")

MPCR_object$ToMatrix(5, 10)
MPCR_object$Row      #5
MPCR_object$Col      #10
MPCR_object$Size     #50
MPCR_object$IsMatrix #TRUE

MPCR_object$PrintValues()
MPCR_object$ToVector()

MPCR_object
```

---

02-MPCRTile

---

*MPCRTile S4 Class*


---

## Description

MPCRTile is a data structure for tile matrices with mixed precision, where each tile possesses a specific precision level.

## Value

MPCRTile object (constructor - accessors - methods)

## Constructor

**new** creates a new instance of Tile-Matrix MPCRTile class.  
**new(MPCRTile, rows, cols, rows\_per\_tile, cols\_per\_tile, values, precisions)**  
**rows** Number of rows in the matrix.  
**cols** Number of cols in the matrix.  
**rows\_per\_tile** Number of rows in each tile.  
**cols\_per\_tile** Number of cols in each tile.  
**values** R matrix or vector containing all the values that should be in the matrix.  
**precisions** R matrix or vector of strings, containing precision type of each tile.

## Accessors

The following accessors can be used to get the values of the slots:

**Size** Total number of elements inside the Matrix.  
**Row** Number of rows.

Col Number of cols.  
 TileRow Number of rows in each tile.  
 TileCol Number of cols in each tile.  
 TileSize Total number of elements in each tile.

## Methods

The following methods are available for objects of class MPCRTile:

### PrintTile:

`PrintTile(tile_row_idx, tile_col_idx)`: Prints all the values stored inside a specific tile plus meta-data about the tile.

`tile_row_idx` Row index of the tile.  
`tile_col_idx` Col index of the tile.

### ChangeTilePrecision:

`ChangeTilePrecision(tile_row_idx, tile_col_idx, precision)`: Change the precision of specific tile, this function will need to copy all the values to cast them to the new precision.

`tile_row_idx` Row index of the tile.  
`tile_col_idx` Col index of the tile.  
`precision` Required new precision as a string.

### FillSquareTriangle:

`FillSquareTriangle(value, upper.tri, precision)`: Fills upper or lower triangle with a given value and precision, new tiles will be created, replacing the old tiles. **Note:** The input must be a square matrix

`value` A value used during matrix filling.  
`upper.tri` A flag to indicate what triangle to fill. if TRUE, the upper triangle will be filled, otherwise the lower triangle.  
`precision` The precision of the tiles created during matrix filling, in case it's not a diagonal tile.

**Sum:** `Sum()`: Get the sum of all elements in all tiles in MPCRTile Matrix.

**Prod:** `Prod()`: Get the product of all elements in all tiles in MPCRTile Matrix.

## Examples

```
library(MPCR)
# Example usage of the class and its methods
a <- matrix(1:36, 6, 6)
b <- c("double", "double", "single", "double",
      "half", "double", "half", "double",
```

```

"single")

tile_mat <- new(MPCRTile, 6, 6, 2, 2, a, b)
tile_mat
sum <- tile_mat$Sum()
prod <- tile_mat$Prod()
tile_mat$PrintTile(1,1)
tile_mat$ChangeTilePrecision(1,1,"single")

n_rows <- tile_mat$Row
n_cols <- tile_mat$Col
total_size <- tile_mat$Size
rows_per_tile <- tile_mat$TileRow
cols_per_tile <- tile_mat$TileCol

```

03-Converters

*Converters***Description**

Converters from R to MPCR objects and vice-versa.

**Value**

An MPCR or R numeric vector/matrix.

**MPCR Converter**

Convert R object to MPCR object.

**MPCR converters:**

`as.MPCR(data, nrow = 0, ncol = 0, precision)`: Converts R object to MPCR object.

`data` R matrix/vector.

`nrow` Number of rows of the new MPCR matrix, **default = zero** which means a vector will be created.

`ncol` Number of cols of the new MPCR matrix, **default = zero** which means a vector will be created.

`precision` String indicates the precision of the new MPCR object (half, single, or double).

**R Converter**

Convert an MPCR object to R object.

**R vector converter:**

`MPCR.ToNumericVector(x)`: Converts an MPCR object to a numeric R vector.

`x` MPCR object.

**R matrix converter:**

`MPCR.ToNumericMatrix(x)`: Converts an MPCR object to a numeric R matrix.

`x` MPCR object.

**Examples**

```
# Example usage of the class and its methods
library(MPCR)
a <- matrix(1:36, 6, 6)
MPCR_matrix <- as.MPCR(a,nrow=6,ncol=6,precision="single")
r_vector <- MPCR.ToNumericVector(MPCR_matrix)
r_vector
r_matrix <- MPCR.ToNumericMatrix(MPCR_matrix)
r_matrix
```

04-Arithmetic

*Binary arithmetic numeric/MPCR objects.***Description**

Binary arithmetic for numeric/MPCR objects.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
e1 + e2

## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
e1 - e2

## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
e1 * e2

## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
e1 / e2

## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
e1 ^ e2

## S4 method for signature 'Rcpp_MPCR,BaseLinAlg'
e1 + e2

## S4 method for signature 'Rcpp_MPCR,BaseLinAlg'
e1 * e2

## S4 method for signature 'Rcpp_MPCR,BaseLinAlg'
e1 - e2
```

```
## S4 method for signature 'Rcpp_MPCR,BaseLinAlg'
e1 / e2

## S4 method for signature 'Rcpp_MPCR,BaseLinAlg'
e1 ^ e2
```

### Arguments

`e1, e2`                      Numeric/MPCR objects.

### Value

An MPCR object, matching the data type of the highest precision input.

### Examples

```
library(MPCR)
s1 <- as.MPCR(1:20,nrow=2,ncol=10,"single")
s2 <- as.MPCR(21:40,nrow=2,ncol=10,"double")

x <- s1 + s2
typeof(x) # A 64-bit precision (double) MPCR matrix.

s3 <- as.MPCR(1:20,nrow=2,ncol=10,"single")
x <- s1 + s3
typeof(x) # A 32-bit precision (single) MPCR matrix.
```

### Description

Binary comparison operators for numeric/MPCR objects.

### Usage

```
## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
e1 < e2

## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
e1 <= e2

## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
e1 == e2

## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
```



```
e1 != e2

## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
e1 > e2

## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
e1 >= e2

## S4 method for signature 'Rcpp_MPCR,BaseLinAlg'
e1 < e2

## S4 method for signature 'Rcpp_MPCR,BaseLinAlg'
e1 <= e2

## S4 method for signature 'Rcpp_MPCR,BaseLinAlg'
e1 == e2

## S4 method for signature 'Rcpp_MPCR,BaseLinAlg'
e1 != e2

## S4 method for signature 'Rcpp_MPCR,BaseLinAlg'
e1 > e2

## S4 method for signature 'Rcpp_MPCR,BaseLinAlg'
e1 >= e2
```

### Arguments

e1, e2                      Numeric/MPCR objects.

### Value

A vector/matrix of logicals.

### Examples

```
library(MPCR)
s1 <- as.MPCR(1:20,nrow=2,ncol=10,"single")
s2 <- as.MPCR(21:40,nrow=2,ncol=10,"double")

x <- s1 > s2
```

---

06-Extract-Replace *Extract or replace elements from an MPCR object.*


---

**Description**

Extract or replace elements from an MPCR object using the '[', '[[', '[<-', and '[[<-' operators. When extracting values, they will be converted to double precision. However, if you update a single object, the double value will be cast down to match the precision. If the MPCR object is a matrix and you access it using the 'i' index, the operation is assumed to be performed in column-major order, or using 'i' and 'j' index.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
x[i, j, drop = TRUE]
## S4 replacement method for signature 'Rcpp_MPCR'
x[i, j, ...] <- value
## S4 method for signature 'Rcpp_MPCR'
x[[i, drop = TRUE]]
## S4 replacement method for signature 'Rcpp_MPCR'
x[[i, ...]] <- value
```

**Arguments**

x	An MPCR object.
i	Row index or indices.
j	Column index or indices.
...	ignored.
drop	ignored.
value	A value to replace the selected elements with.

**Examples**

```
library(MPCR)
x <- as.MPCR(1:50, precision="single")
ext <- x[5]
x[5] <- 0
x$ToMatrix(5, 10)
x[2, 5]
x[3, 5] <- 100
```

---

07-Dimensions	<i>dimensions</i>
---------------	-------------------

---

**Description**

Returns the number of rows or cols in an MPCR object.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
nrow(x)

## S4 method for signature 'Rcpp_MPCR'
ncol(x)
```

**Arguments**

**x**                      An MPCR object.

**Value**

The number of rows/cols in an MPCR object.

**Examples**

```
library(MPCR)
x <- as.MPCR(1:16,4,4,"single")
y <- as.MPCR(1:20,4,5,"double")
rows_x <- nrow(x)
cols_y <- ncol(y)
```

---

08-Copy	<i>copy</i>
---------	-------------

---

**Description**

Functions for copying MPCR objects.

**Value**

An MPCR copy from the input object.

**MPCR deep copy**

Create a copy of an MPCR object. Typically, using 'equal' creates a new pointer for the object, resulting in any modifications made to object one affecting object two as well.

**copy:**

`MPCR.copy(x)`: Create a new copy of an MPCR object.

`x` MPCR object.

**MPCRTile deep copy**

Create a duplicate of an MPCRTile object. Usually, using 'equal' creates a new pointer for the object, causing any modifications made to object one to affect object two as well.

**copy:**

`MPCRTile.copy(x)`: Create a new copy of an MPCRTile matrix.

`x` MPCRTile matrix.

**Examples**

```
library(MPCR)
# Example usage of the class and its methods
a <- matrix(1:36, 6, 6)
MPCR_matrix <- as.MPCR(a,nrow=6,ncol=6,precision="single")

# Normal equal '=' will create a new pointer of the object, so any change in object A
# will affect object B
temp_MPCR_matrix = MPCR_matrix
temp_MPCR_matrix[2,2] <- 500
MPCR_matrix[2,2]          #500

MPCR_matrix_copy <- MPCR.copy(MPCR_matrix)
MPCR_matrix[2,2] <-100
MPCR_matrix_copy[2,2] <- 200

MPCR_matrix[2,2]          #100
MPCR_matrix_copy[2,2]     #200
```

---

09-Concatenate

*concatenate*


---

**Description**

`c()` function for MPCR objects.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
MPCR.Concatenate(x)
```

**Arguments**

`x`                      List of MPCR objects.

**Value**

MPCR object containing values from all objects in the list.

**Examples**

```
library(MPCR)
x <- as.MPCR(1:20,precision="single")
y <- as.MPCR(1:20,precision="single")
list <- c(x,y)
new_obj <- MPCR.Concatenate(list)
```

10-Bind

*bind***Description**

`rbind()` and `cbind()` for MPCR objects.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
MPCR.rbind(x,y)

## S4 method for signature 'Rcpp_MPCR'
MPCR.cbind(x,y)
```

**Arguments**

`x`                      An MPCR object.  
`y`                      An MPCR object.

**Value**

An MPCR object, matching the data type of the highest precision input.

**Examples**

```
library(MPCR)
# create 2 MPCR matrix a,b
a <- as.MPCR(1:20,nrow=2,ncol=10,"single")
b <- as.MPCR(21:40,nrow=2,ncol=10,"double")

x <- MPCR.rbind(a,b)
y <- MPCR.cbind(a,b)
```

---

11-Diagonal	<i>diag</i>
-------------	-------------

---

**Description**

Returns the diagonal of an MPCR matrix.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
diag(x)
```

**Arguments**

*x*                      An MPCR matrix.

**Value**

An MPCR vector contains the main diagonal of the matrix.

**Examples**

```
library(MPCR)
x <- as.MPCR(1:16,4,4,"single")
diag_vals <- diag(x)
```

---

12-Extremes	<i>Min-Max Functions</i>
-------------	--------------------------

---

**Description**

Min-Max functions for MPCR objects values and indices, all NA values are disregarded.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
min(x)
```

```
## S4 method for signature 'Rcpp_MPCR'
max(x)
```

```
## S4 method for signature 'Rcpp_MPCR'
which.min(x)
```

```
## S4 method for signature 'Rcpp_MPCR'
which.max(x)
```

**Arguments**

`x`                      An MPCR object.

**Value**

Min/max value/index.

**Examples**

```
library(MPCR)

x <- as.MPCR(1:20,precision="double")
min <- min(x)
min_idx <- which.min(x)
```

---

13-Log

---

*Logarithms and Exponentials*


---

**Description**

exp/log functions.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
exp(x)

## S4 method for signature 'Rcpp_MPCR'
expm1(x)

## S4 method for signature 'Rcpp_MPCR'
log(x, base = 1)

## S4 method for signature 'Rcpp_MPCR'
log10(x)

## S4 method for signature 'Rcpp_MPCR'
log2(x)
```

**Arguments**

`x`                      An MPCR object.

`base`                  The logarithm base. If `base = 1`, `exp(1)` is assumed, only base 1,2, and 10 available.

**Value**

An MPCR object of the same dimensions as the input.

**Examples**

```
library(MPCR)

x <- as.MPCR(1:20,precision="double")
log(x)
```

---

14-Mathis

*Finite, infinite, and NaNs*

---

**Description**

Finite, infinite, and NaNs.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
is.finite(x)

## S4 method for signature 'Rcpp_MPCR'
is.infinite(x)

## S4 method for signature 'Rcpp_MPCR'
is.nan(x)
```

**Arguments**

x                      An MPCR object.

**Value**

A bool vector/matrix of the same dimensions as the input.

**Examples**

```
library(MPCR)

x <- as.MPCR(1:20,precision="double")
is.nan(sqrt(x))
```



**Description**

Miscellaneous mathematical functions.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
abs(x)

## S4 method for signature 'Rcpp_MPCR'
sqrt(x)
```

**Arguments**

`x`                      An MPCR object.

**Value**

An MPCR object of the same dimensions as the input.

**Examples**

```
library(MPCR)

x <- as.MPCR(1:20,precision="double")
sqrt(x)
```

**Description**

`is.na()`, `na.omit()`, and `na.exclude()` for MPCR objects.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
MPCR.is.na(object,index=-1)
## S4 method for signature 'Rcpp_MPCR'
MPCR.na.exclude(object,value)
## S4 method for signature 'Rcpp_MPCR'
MPCR.na.omit(object)
```

**Arguments**

<code>object</code>	MPCR object.
<code>index</code>	If a particular index in the MPCR matrix/vector is specified, it will be checked. If no index is provided, all elements will be checked.
<code>value</code>	Value to replace all NAN with.

**Value**

MPCR.is.na will return matrix/vector/bool according to input of the function.  
MPCR.na.exclude & MPCR.na.omit will not return anything.

**Examples**

```
library(MPCR)
x <- as.MPCR(1:20,precision="single")
x[1] <- NAN
MPCR.is.na(x, index=1) #TRUE
MPCR.na.exclude(x, 50)
x[1] #50
```

---

17-Replicate

*replicate*


---

**Description**

Replicates the given input number of times according to count/len , only one should be set at a time, and in case both values are given, only the len value will have effect.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
rep(x, count=0, len=0)
```

**Arguments**

<code>x</code>	An MPCR object.
<code>count</code>	Value to determine how many times the input value will be replicated.
<code>len</code>	Value to determine the required output size, the input will be replicated until it matches the output len size.

**Value**

MPCR vector containing the replicated values.

**Examples**

```
library(MPCR)
x <- as.MPCR(1:16,4,4,"single")
rep_vals_1 <- rep(x,count=2) #output size will be 16*2
rep_vals_2 <- rep(x,len=2)  #output size will be 2
```

18-Round

*Rounding functions***Description**

Rounding functions.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
ceiling(x)

## S4 method for signature 'Rcpp_MPCR'
floor(x)

## S4 method for signature 'Rcpp_MPCR'
trunc(x)

## S4 method for signature 'Rcpp_MPCR'
round(x, digits = 0)
```

**Arguments**

<code>x</code>	An MPCR object.
<code>digits</code>	The number of digits to use in rounding.

**Value**

An MPCR object of the same dimensions as the input.

**Examples**

```
library(MPCR)

input <- runif(20,-1,1)
x <- as.MPCR(input,precision="double")
floor(x)
```

19-Scale

*scale***Description**

Center or scale an MPCR object.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
scale(x, center, scale)
```

**Arguments**

*x*                      An MPCR object.  
*center, scale*                      Logical or MPCR objects.

**Value**

An MPCR matrix.

**Examples**

```
library(MPCR)
input <- as.MPCR(1:50, precision="single")
x$ToMatrix(5, 10)
temp_center_scale <- new(1:10, precision="double")
z <- scale(x=input, center=FALSE, scale=temp_center_scale)
```

20-Sweep

*sweep***Description**

Sweep an MPCR vector through an MPCR matrix.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
sweep(x, stat, margin, FUN)
```

**Arguments**

<code>x</code>	An MPCR object.
<code>stat</code>	MPCR vector containing the value(s) that should be used in the operation.
<code>margin</code>	1 means row; otherwise means column.
<code>FUN</code>	Sweeping function; must be one of "+", "-", "*", "/", or "^".

**Value**

An MPCR matrix of the same type as the highest precision input.

**Examples**

```
library(MPCR)
x <- as.MPCR(1:20,10,2,"single")
y <- as.MPCR(1:5,precision="double")
sweep_out <- sweep(x, stat=y, margin=1, FUN="+")
MPCR.is.double(sweep_out) #TRUE
```

---

21-Special Math      *Special mathematical functions.*

---

**Description**

Special mathematical functions.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
gamma(x)

## S4 method for signature 'Rcpp_MPCR'
lgamma(x)
```

**Arguments**

<code>x</code>	An MPCR object.
----------------	-----------------

**Value**

An MPCR object of the same dimensions as the input.

**Examples**

```
library(MPCR)

x <- as.MPCR(1:20,precision="double")
lgamma(x)
```

**Description**

Basic trig functions.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
sin(x)

## S4 method for signature 'Rcpp_MPCR'
cos(x)

## S4 method for signature 'Rcpp_MPCR'
tan(x)

## S4 method for signature 'Rcpp_MPCR'
asin(x)

## S4 method for signature 'Rcpp_MPCR'
acos(x)

## S4 method for signature 'Rcpp_MPCR'
atan(x)
```

**Arguments**

`x`                      An MPCR object.

**Value**

An MPCR object of the same dimensions as the input.

**Examples**

```
library(MPCR)

mpcr_matrix <- as.MPCR(1:20,nrow=2,ncol=10,"single")
x <- sin(mpcr_matrix)
```

**Description**

These functions give the obvious hyperbolic functions. They respectively compute the hyperbolic cosine, sine, tangent, and their inverses, arc-cosine, arc-sine, arc-tangent (or 'area cosine', etc).

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
sinh(x)
## S4 method for signature 'Rcpp_MPCR'
cosh(x)
## S4 method for signature 'Rcpp_MPCR'
tanh(x)
## S4 method for signature 'Rcpp_MPCR'
asinh(x)
## S4 method for signature 'Rcpp_MPCR'
acosh(x)
## S4 method for signature 'Rcpp_MPCR'
atanh(x)
```

**Arguments**

`x`                      An MPCR object.

**Value**

An MPCR object of the same dimensions as the input.

**Examples**

```
library(MPCR)

mpcr_matrix <- as.MPCR(1:20,nrow=2,ncol=10,precision="single")
x <- sinh(mpcr_matrix)
```

---

24-Transpose	<i>transpose</i>
--------------	------------------

---

**Description**

Transpose an MPCR object.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
t(x)
```

**Arguments**

**x**                      An MPCR object.

**Value**

An MPCR object.

**Examples**

```
library(MPCR)
a <- matrix(1:20, nrow = 2)
a_MPCR <- as.MPCR(a, 2, 10, "double")
a_MPCR_transpose <- t(a_MPCR)
```

---

25-Check precision	<i>Metadata functions</i>
--------------------	---------------------------

---

**Description**

Checks the precision of a given MPCR object.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
MPCR.is.single(x)
## S4 method for signature 'Rcpp_MPCR'
MPCR.is.half(x)
## S4 method for signature 'Rcpp_MPCR'
MPCR.is.double(x)
## S4 method for signature 'Rcpp_MPCR'
MPCR.is.float(x)
```



**Arguments**

`x`                      An MPCR object.

**Value**

Boolean indicates the precision of the object according to the used function.

**Examples**

```
library(MPCR)
x <- as.MPCR(1:20,precision="double")
MPCR.is.double(x) #TRUE
MPCR.is.single(x) #FALSE
```

---

26-Metadata

---

*Metadata functions*


---

**Description**

Metadata functions.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
storage.mode(x)
## S4 method for signature 'Rcpp_MPCR'
typeof(x)
## S4 method for signature 'Rcpp_MPCR'
MPCR.object.size(x)
## S4 method for signature 'Rcpp_MPCR'
MPCR.ChangePrecision(x,precision)
```

**Arguments**

`x`                      An MPCR object.

`precision`            String with the required precision.

**Value**

Prints/change metadata about an MPCR object.

**Examples**

```
library(MPCR)

x <- as.MPCR(1:20,precision="double")
typeof(x)
MPCR.ChangePrecision(x,"single")
MPCR.is.single(x) #True
```

---

27-Print

---

*print*


---

**Description**

Prints the precision and type of the object, and `print` will print the meta data of the object without printing the values. Function `x$PrintValues()` should be used to print the values."

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
print(x)

## S4 method for signature 'Rcpp_MPCR'
show(object)
```

**Arguments**

`x`, `object`      An MPCR objects.

**Details**

Prints metadata about the object and some values.

**Value**

A string containing the metadata of the MPCR object.

**Examples**

```
library(MPCR)
x <- as.MPCR(1:16,4,4,"single")
y <- as.MPCR(1:20,4,5,"double")
x
print(y)
```

---

```
28-Cholesky decomposition
      cholesky decomposition
```

---

**Description**

Performs the Cholesky factorization of a positive definite MPCR matrix `x`.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
chol(x, upper_triangle=TRUE)
```

**Arguments**

`x`                      An MPCR matrix.  
`upper_triangle`        Boolean to check on which triangle the cholesky decomposition should be applied.

**Value**

An MPCR matrix.

**Examples**

```
library(MPCR)
x <- as.MPCR(c(1.21, 0.18, 0.13, 0.41, 0.06, 0.23,
               0.18, 0.64, 0.10, -0.16, 0.23, 0.07,
               0.13, 0.10, 0.36, -0.10, 0.03, 0.18,
               0.41, -0.16, -0.10, 1.05, -0.29, -0.08,
               0.06, 0.23, 0.03, -0.29, 1.71, -0.10,
               0.23, 0.07, 0.18, -0.08, -0.10, 0.36), 6, 6, precision="double")
chol_out <- chol(x)
```

---

```
29-Cholesky inverse
      cholesky inverse
```

---

**Description**

Performs the inverse of the original matrix using the Cholesky factorization of an MPCR matrix `x`.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
chol2inv(x, size = NCOL(x))
```

**Arguments**

**x**                      An MPCR object.

**size**                  The number of columns to use.

**Value**

An MPCR object.

**Examples**

```
library(MPCR)
x <- as.MPCR(c(1.21, 0.18, 0.13, 0.41, 0.06, 0.23,
               0.18, 0.64, 0.10, -0.16, 0.23, 0.07,
               0.13, 0.10, 0.36, -0.10, 0.03, 0.18,
               0.41, -0.16, -0.10, 1.05, -0.29, -0.08,
               0.06, 0.23, 0.03, -0.29, 1.71, -0.10,
               0.23, 0.07, 0.18, -0.08, -0.10, 0.36), 6, 6, precision="single")
chol_out <- chol(x)
chol <- chol2inv(chol_out)
```

---

30-Crossprod

*crossprod*


---

**Description**

Calculates the cross product of two MPCR matrices. It uses BLAS routine `gemm()` for **A X B** operations and `syrk()` for **A X A<sup>T</sup>** operations.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
crossprod(x, y = NULL)

## S4 method for signature 'Rcpp_MPCR'
tcrossprod(x, y = NULL)
```

**Arguments**

**x**                      An MPCR object.

**y**                      Either NULL, or an MPCR matrix.

**Details**

Calculates cross product of two MPCR matrices performs:

$x \%*\% y, t(x) \%*\% x$

This function uses blas routine `gemm()` for  $A X B$  operations & `syrk()` for  $A X A^T$  operations.

**Value**

An MPCR matrix.

**Examples**

```
library(MPCR)
x <- as.MPCR(1:16,4,4,"single")
y <- as.MPCR(1:20,4,5,"double")

z <- crossprod(x)      # t(x) x
z <- tcrossprod(x)     # x t(x)
z <- crossprod(x,y)    # x y
z <- x \%*\% y         # x y
```

---

31-Eigen decomposition  
*eigen decomposition*

---

**Description**

Solves a system of equations or invert an MPCR matrix, using lapack routine `syevr()`

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
eigen(x, only.values = FALSE)
```

**Arguments**

`x`                    An MPCR object.  
`only.values`        (TRUE/FALSE)?

**Value**

A list contains MPCR objects describing the values and optionally vectors.

**Examples**

```
library(MPCR)
s <- runif(10, 3)
cross_prod <- crossprod(s)
x <- as.MPCR(cross_prod, nrow(cross_prod), nrow(cross_prod), precision)
y <- eigen(x)
```

---

32-Symmetric	<i>isSymmetric</i>
--------------	--------------------

---

**Description**

Check if a given MPCR matrix is symmetric.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
isSymmetric(object, ...)
```

**Arguments**

<code>object</code>	An MPCR matrix.
<code>...</code>	Ignored.

**Value**

A logical value.

**Examples**

```
library(MPCR)

x <- as.MPCR(1:50, 25, 2, "Single")
isSymmetric(x) #false

crossprod_output <- crossprod(x)
isSymmetric(crossprod_output) #true
```

33-Norm

*norm***Description**

Compute norm.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
norm(x, type = "O")
```

**Arguments**

**x**                    An MPCR object.  
**type**                "O"-ne, "I"-nfinity, "F"-robenius, "M"-ax modulus, and "l" norms.

**Value**

An MPCR object.

**Examples**

```
library(MPCR)

x <- as.MPCR(1:20, precision="double")
norm(x, type="O")
```

34-QR decomposition

*QR decomposition***Description**

QR factorization and related functions.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
qr(x, tol = 1e-07)

## S4 method for signature 'ANY'
qr.Q(qr, complete = FALSE, Dvec)

## S4 method for signature 'ANY'
qr.R(qr, complete = FALSE)
```

**Arguments**

<code>x</code>	An MPCR matrix.
<code>qr</code>	QR decomposition MPCR object.
<code>tol</code>	The tolerance for determining numerical column rank.
<code>complete</code>	Should the complete or truncated factor be returned?
<code>Dvec</code>	Vector of diagonals to use when re-constructing Q ( <b>default is 1's</b> ).

**Details**

The factorization is performed by the LAPACK routine `geqp3()`. This should be similar to calling `qr()` on an ordinary R matrix with the argument `LAPACK=TRUE`.

**Value**

`qr`                      Output of `qr()`.

**Examples**

```
library(MPCR)

qr_input <- as.MPCR( c(1, 2, 3, 2, 4, 6, 3, 3, 3), 3, 3, "single")
qr_out <- qr(qr_input)
qr_out
qr_out[["qr"]]$PrintValues()
qr_out[["qraux"]]$PrintValues()
qr_out[["pivot"]]$PrintValues()
qr_out[["rank"]]$PrintValues()

qr_q <- qr.Q(qr_out)
qr_q
```

---

35-Reciprocal condition

*reciprocal condition*


---

**Description**

Compute matrix norm.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
rcond(x, norm = "O", useInv = FALSE)
```



**Arguments**

<code>x</code>	An MPCR object.
<code>norm</code>	"O"-ne or "I"-nfinity norm.
<code>useInv</code>	TRUE to use the lower triangle only.

**Value**

An MPCR Object.

**Examples**

```
library(MPCR)

x <- as.MPCR(1:20,precision="double")
rcond(x)
```

---

36-Solve

*solve*


---

**Description**

Solve a system of equations or invert an MPCR matrix.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
solve(a, b = NULL, ...)
```

**Arguments**

<code>a, b</code>	An MPCR objects.
<code>...</code>	Ignored.

**Value**

Solves the equation  $AX=B$  .and if  $B=NULL$   $t(A)$  will be used.

**Examples**

```
library(MPCR)

x <- as.MPCR(1:20,4,5,"double")
y <- crossprod(x)
solve(y)
```

---

## 37-Singular value decomposition

### *SVD*

---

**Description**

SVD factorization.

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
La.svd(x, nu = min(n, p), nv = min(n, p))

## S4 method for signature 'Rcpp_MPCR'
svd(x, nu = min(n, p), nv = min(n, p))
```

**Arguments**

<code>x</code>	An MPCR matrix.
<code>nu, nv</code>	The number of left/right singular vectors to return.

**Details**

The factorization is performed by the LAPACK routine `gesdd()`.

**Value**

The SVD decomposition of the MPCR matrix.

**Examples**

```
library(MPCR)
svd_vals <- c(1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 0, 0, 0,
              0, 0, 0, 0, 0, 0, 1, 1, 1, 0, 0, 0, 0, 0, 0,
              0, 0, 0, 1, 1, 1)

x <- as.MPCR(svd_vals, 9, 4, "single")
y <- svd(x)
```

---

38-Back/Forward solve

*Back/Forward solve*


---

## Description

Solves a system of linear equations where the coefficient matrix is upper or lower triangular. The function solves the equation  $A X = B$ , where  $A$  is the coefficient matrix,  $X$  is the solution vector, and  $B$  is the right-hand side vector.

## Usage

```
## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
backsolve(r, x, k = ncol(r), upper.tri = TRUE, transpose = FALSE)

## S4 method for signature 'Rcpp_MPCR,Rcpp_MPCR'
forwardsolve(l, x, k = ncol(l), upper.tri = FALSE, transpose = FALSE)
```

## Arguments

<code>l</code>	An MPCR object.
<code>r</code>	An MPCR object.
<code>x</code>	An MPCR object whose columns give the right-hand sides for the equations.
<code>k</code>	The number of columns of <code>r</code> and rows of <code>x</code> to use.
<code>upper.tri</code>	logical; if TRUE, the upper triangular part of <code>r</code> is used. Otherwise, the lower one.
<code>transpose</code>	logical; if TRUE, solve for $t(l, r)$ %*% output == <code>x</code> .

## Value

An MPCR object represents the solution to the system of linear equations.

## Examples

```
library(MPCR)
a <- matrix(c(2, 0, 0, 3), nrow = 2)
b <- matrix(c(1, 2), nrow = 2)
a_MPCR <- as.MPCR(a, 2, 2, "single")
b_MPCR <- as.MPCR(b, 2, 1, "double")
x <- forwardsolve(a_MPCR, b_MPCR)
x
```

**Description**

Performs matrix-matrix multiplication of two given MPCR matrices to performs:

$C = \alpha A * B + \beta C$

$C = \alpha A A^T + \beta C$

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
MPCR.gemm(a,b = NULL,c,transpose_a= FALSE,transpose_b=FALSE,alpha=1,beta=0)
```

**Arguments**

<code>a</code>	An MPCR matrix A.
<code>b</code>	An MPCR matrix B, if NULL, the function will perform syrk operation from blas.
<code>c</code>	Input/Output MPCR matrix C.
<code>transpose_a</code>	A flag to indicate whether transpose matrix A should be used, if B is NULL and <code>transpose_a=TRUE</code> The function will perform the following operation: <b><math>C = \alpha A^T X A + \beta C</math></b> .
<code>transpose_b</code>	A flag to indicate whether transpose matrix B should be used.
<code>alpha</code>	Specifies the scalar alpha.
<code>beta</code>	Specifies the scalar beta.

**Value**

An MPCR matrix.

**Examples**

```
library(MPCR)
# create 3 MPCR matrices a,b,c
print(c)
MPCR.gemm(a,b,c,transpose_a=false,transpose_b=TRUE,alpha=1,beta=1)
print(c)
```

40-MPCR TRSM

*MPCR TRSM (Triangular Solve)***Description**

Solves a triangular matrix equation.

performs:

$\text{op}(A) * X = \alpha * B$

$X * \text{op}(A) = \alpha * B$

**Usage**

```
## S4 method for signature 'Rcpp_MPCR'
MPCR.trsm(a,b,upper_triangle,transpose,side = 'L',alpha =1)
```

**Arguments**

a	MPCR Matrix A.
b	MPCR Matrix B.
upper_triangle	If the value is TRUE, the referenced part of matrix A corresponds to the upper triangle, with the opposite triangle assumed to contain zeros.
transpose	If TRUE, the transpose of A is used.
side	'R' for Right side, 'L' for Left side.
alpha	Factor used for A, If alpha is zero, A is not accessed.

**Value**

An MPCR Matrix.

**Examples**

```
library(MPCR)
a <- matrix(c(3.12393, -1.16854, -0.304408, -2.15901,
              -1.16854, 1.86968, 1.04094, 1.35925,
              -0.304408, 1.04094, 4.43374, 1.21072,
              -2.15901, 1.35925, 1.21072, 5.57265), 4,4)

mat_a <- as.MPCR(a,4,4,"single")
mat_b <- as.MPCR(a,4,4,"double")

MPCRTile.trsm(a=mat_a,b=mat_b,side='R',upper_triangle=TRUE,transpose=FALSE,alpha=1)
print(mat_b)
```

---

41-MPCRTile GEMM     *MPCRTile GEMM (Matrix-Matrix Multiplication)*


---

### Description

Tile-based matrix-matrix multiplication of two given MPCR tiled matrices to **perform**:  
 $C = \alpha * A \times B + \beta * C$

### Usage

```
## S4 method for signature 'Rcpp_MPCRTile'
MPCRTile.gemm(a,b,c,transpose_a= FALSE,transpose_b=FALSE,alpha=1,beta=0,num_threads
```

### Arguments

a	An MPCR tile matrix A.
b	An MPCR tile matrix B.
c	Input/Output MPCR tile matrix C.
transpose_a	A flag to indicate whether transpose matrix A should be used.
transpose_b	A flag to indicate whether transpose matrix B should be used.
alpha	Specifies the scalar alpha.
beta	Specifies the scalar beta.
num_threads	An integer to determine number of thread to run using openmp, default = 1 (serial with no parallelization).

### Value

An MPCR tile matrix C.

### Examples

```
library(MPCR)
# create 3 MPCR Tile matrices a,b,c
a <- as.MPCR(1:20,5,4,"single")
b <- as.MPCR(1:20,4,5,"single")
c <- as.MPCR(1:16,4,4,"single")
print(c)
MPCRTile.gemm(a,b,c,transpose_a=false,transpose_b=TRUE,alpha=1,beta=1,num_threads = 8)
print(c)
```

---

42-MPCRTile POTRF    *MPCRTile Chol ( Cholesky decomposition )*


---

## Description

Tile-based Cholesky decomposition of a positive definite tile-based symmetric matrix.

## Usage

```
## S4 method for signature 'Rcpp_MPCRTile'
chol(x, overwrite_input = TRUE, num_threads = 1)
```

## Arguments

**x**                    An MPCRT tile matrix.

**overwrite\_input**    A flag to determine whether to overwrite the input ( TRUE ), or return a new MPCRT tile matrix.

**num\_threads**        An integer to determine number of thread to run using openmp, default = 1 (serial with no parallelization).

## Value

An MPCRT tile matrix.

## Examples

```
library(MPCR)
a <- matrix(c(1.21, 0.18, 0.13, 0.41, 0.06, 0.23,
              0.18, 0.64, 0.10, -0.16, 0.23, 0.07,
              0.13, 0.10, 0.36, -0.10, 0.03, 0.18,
              0.41, -0.16, -0.10, 1.05, -0.29, -0.08,
              0.06, 0.23, 0.03, -0.29, 1.71, -0.10,
              0.23, 0.07, 0.18, -0.08, -0.10, 0.36), 6, 6)
b <- c("float", "double", "float", "float",
       "double", "double", "float", "float",
       "double")

chol_mat <- new(MPCRTile, 6, 6, 2, 2, a, b)

x <- chol(chol_mat, overwrite_input=FALSE, num_threads=8)
print(chol_mat)
print(x)

chol(chol_mat)
print(chol_mat)
```

---

43-MPCRTile TRSM     *MPCRTile TRSM (Triangular Solve)*


---

**Description**

Tile-based algorithm to solve a triangular matrix equation for MPCRT tiled matrices.  
performs:  
 $\text{op}(A) * X = \alpha * B$   
 $X * \text{op}(A) = \alpha * B$

**Usage**

```
## S4 method for signature 'Rcpp_MPCRTile'
MPCRTile.trsm(a,b,side,upper_triangle,transpose,alpha)
```

**Arguments**

a	An MPCRT tile matrix A.
b	An MPCRT tile matrix B, X after returning.
side	'R' for right side, 'L' for left side.
upper_triangle	What part of the matrix A is referenced (if TRUE upper triangle is referenced), the opposite triangle being assumed to be zero.
transpose	If TRUE, the transpose of A is used.
alpha	Factor used for A, If alpha is zero, A is not accessed.

**Value**

An MPCRT Tile Matrix B ->(X).

**Examples**

```
library(MPCR)
a <- matrix(c(3.12393, -1.16854, -0.304408, -2.15901,
              -1.16854, 1.86968, 1.04094, 1.35925,
              -0.304408, 1.04094, 4.43374, 1.21072,
              -2.15901, 1.35925, 1.21072, 5.57265), 4,4)

b <- c("float", "double", "float", "float")
c <- c("float", "float", "double", "float")

mat_a <- new(MPCRTile, 4,4, 2, 2, a, b)
mat_b <- new(MPCRTile, 4,4, 2, 2, a, c)

MPCRTile.trsm(a=mat_a,b=mat_b,side='R',upper_triangle=TRUE,transpose=FALSE,alpha=1)
```



```
print(mat_b)
```

# Index

!=, Rcpp\_MPCR, BaseLinAlg-method  
     (05-Comparison), 8  
 !=, Rcpp\_MPCR, Rcpp\_MPCR-method  
     (05-Comparison), 8  
 \*Topic **S4 class**  
     01-MPCR, 3  
     02-MPCRTile, 4  
 \*, Rcpp\_MPCR, BaseLinAlg-method  
     (04-Arithmetic), 7  
 \*, Rcpp\_MPCR, Rcpp\_MPCR-method  
     (04-Arithmetic), 7  
 +, Rcpp\_MPCR, BaseLinAlg-method  
     (04-Arithmetic), 7  
 +, Rcpp\_MPCR, Rcpp\_MPCR-method  
     (04-Arithmetic), 7  
 -, Rcpp\_MPCR, BaseLinAlg-method  
     (04-Arithmetic), 7  
 -, Rcpp\_MPCR, Rcpp\_MPCR-method  
     (04-Arithmetic), 7  
 /, Rcpp\_MPCR, BaseLinAlg-method  
     (04-Arithmetic), 7  
 /, Rcpp\_MPCR, Rcpp\_MPCR-method  
     (04-Arithmetic), 7  
 <, Rcpp\_MPCR, BaseLinAlg-method  
     (05-Comparison), 8  
 <, Rcpp\_MPCR, Rcpp\_MPCR-method  
     (05-Comparison), 8  
 <=, Rcpp\_MPCR, BaseLinAlg-method  
     (05-Comparison), 8  
 <=, Rcpp\_MPCR, Rcpp\_MPCR-method  
     (05-Comparison), 8  
 ==, Rcpp\_MPCR, BaseLinAlg-method  
     (05-Comparison), 8  
 ==, Rcpp\_MPCR, Rcpp\_MPCR-method  
     (05-Comparison), 8  
 >, Rcpp\_MPCR, BaseLinAlg-method  
     (05-Comparison), 8  
 >, Rcpp\_MPCR, Rcpp\_MPCR-method  
     (05-Comparison), 8  
 >=, Rcpp\_MPCR, BaseLinAlg-method  
     (05-Comparison), 8  
 >=, Rcpp\_MPCR, Rcpp\_MPCR-method  
     (05-Comparison), 8  
 [, Rcpp\_MPCR-method  
     (06-Extract-Replace), 10  
 [<-, Rcpp\_MPCR-method  
     (06-Extract-Replace), 10  
 [[, Rcpp\_MPCR-method  
     (06-Extract-Replace), 10  
 [[<-, Rcpp\_MPCR-method  
     (06-Extract-Replace), 10  
 ^, Rcpp\_MPCR, BaseLinAlg-method  
     (04-Arithmetic), 7  
 ^, Rcpp\_MPCR, Rcpp\_MPCR-method  
     (04-Arithmetic), 7  
 01-MPCR, 3  
 02-MPCRTile, 4  
 03-Converters, 6  
 04-Arithmetic, 7  
 05-Comparison, 8  
 06-Extract-Replace, 10  
 07-Dimensions, 11  
 08-Copy, 11  
 09-Concatenate, 12  
 10-Bind, 13  
 11-Diagonal, 14  
 12-Extremes, 14  
 13-Log, 15  
 14-Mathis, 16  
 15-Miscmath, 17  
 16-NA's, 17  
 17-Replicate, 18  
 18-Round, 19  
 19-Scale, 20  
 20-Sweep, 20  
 21-Special Math, 21  
 22-Trig, 22  
 23-Hyperbolic, 23

- 24-Transpose, [24](#)
- 25-Check precision, [24](#)
- 26-Metadata, [25](#)
- 27-Print, [26](#)
- 28-Cholesky decomposition, [27](#)
- 29-Cholesky inverse, [27](#)
- 30-Crossprod, [28](#)
- 31-Eigen decomposition, [29](#)
- 32-Symmetric, [30](#)
- 33-Norm, [31](#)
- 34-QR decomposition, [31](#)
- 35-Reciprocal condition, [32](#)
- 36-Solve, [33](#)
- 37-Singular value decomposition, [34](#)
- 38-Back/Forward solve, [35](#)
- 39-MPCR GEMM, [36](#)
- 40-MPCR TRSM, [37](#)
- 41-MPCRTile GEMM, [38](#)
- 42-MPCRTile POTRF, [39](#)
- 43-MPCRTile TRSM, [40](#)
  
- abs, Rcpp\_MPCR-method  
([15-Miscmath](#)), [17](#)
- acos, Rcpp\_MPCR-method ([22-Trig](#)),  
[22](#)
- acosh, Rcpp\_MPCR-method  
([23-Hyperbolic](#)), [23](#)
- arithmetic ([04-Arithmetic](#)), [7](#)
- as.MPCR ([03-Converters](#)), [6](#)
- asin, Rcpp\_MPCR-method ([22-Trig](#)),  
[22](#)
- asinh, Rcpp\_MPCR-method  
([23-Hyperbolic](#)), [23](#)
- atan, Rcpp\_MPCR-method ([22-Trig](#)),  
[22](#)
- atanh, Rcpp\_MPCR-method  
([23-Hyperbolic](#)), [23](#)
  
- backsolve, Rcpp\_MPCR, Rcpp\_MPCR-method  
([38-Back/Forward solve](#)), [35](#)
  
- ceiling, Rcpp\_MPCR-method  
([18-Round](#)), [19](#)
- Check Precision ([25-Check  
precision](#)), [24](#)
- chol ([28-Cholesky decomposition](#)),  
[27](#)
- chol, Rcpp\_MPCR-method  
([28-Cholesky  
decomposition](#)), [27](#)
- chol, Rcpp\_MPCRTile-method  
([42-MPCRTile POTRF](#)), [39](#)
- chol2inv ([29-Cholesky inverse](#)), [27](#)
- chol2inv, Rcpp\_MPCR-method  
([29-Cholesky inverse](#)), [27](#)
- comparison ([05-Comparison](#)), [8](#)
- concatenate ([09-Concatenate](#)), [12](#)
- Converters ([03-Converters](#)), [6](#)
- copy ([08-Copy](#)), [11](#)
- cos, Rcpp\_MPCR-method ([22-Trig](#)), [22](#)
- cosh, Rcpp\_MPCR-method  
([23-Hyperbolic](#)), [23](#)
- crossprod ([30-Crossprod](#)), [28](#)
- crossprod, Rcpp\_MPCR-method  
([30-Crossprod](#)), [28](#)
  
- diag ([11-Diagonal](#)), [14](#)
- diag, Rcpp\_MPCR-method  
([11-Diagonal](#)), [14](#)
- dimensions ([07-Dimensions](#)), [11](#)
  
- eigen ([31-Eigen decomposition](#)), [29](#)
- eigen, Rcpp\_MPCR-method ([31-Eigen  
decomposition](#)), [29](#)
- exp, Rcpp\_MPCR-method ([13-Log](#)), [15](#)
- expm1, Rcpp\_MPCR-method ([13-Log](#)),  
[15](#)
- extremes ([12-Extremes](#)), [14](#)
  
- floor, Rcpp\_MPCR-method  
([18-Round](#)), [19](#)
- forwardsolve, Rcpp\_MPCR, Rcpp\_MPCR-method  
([38-Back/Forward solve](#)), [35](#)
  
- gamma, Rcpp\_MPCR-method  
([21-Special Math](#)), [21](#)
  
- hyperbolic ([23-Hyperbolic](#)), [23](#)
  
- is.finite, Rcpp\_MPCR-method  
([14-Mathis](#)), [16](#)
- is.infinite, Rcpp\_MPCR-method  
([14-Mathis](#)), [16](#)
- is.nan, Rcpp\_MPCR-method  
([14-Mathis](#)), [16](#)
- isSymmetric ([32-Symmetric](#)), [30](#)

- `isSymmetric`, Rcpp\_MPCR-method  
(32-Symmetric), 30
- `La.svd`, Rcpp\_MPCR-method  
(37-Singular value decomposition), 34
- `lgamma`, Rcpp\_MPCR-method  
(21-Special Math), 21
- `log` (13-Log), 15
- `log`, Rcpp\_MPCR-method (13-Log), 15
- `log10`, Rcpp\_MPCR-method (13-Log), 15
- `log2`, Rcpp\_MPCR-method (13-Log), 15
- `mathis` (14-Mathis), 16
- `max`, Rcpp\_MPCR-method  
(12-Extremes), 14
- `metadata` (26-Metadata), 25
- `min`, Rcpp\_MPCR-method  
(12-Extremes), 14
- `miscmath` (15-Miscmath), 17
- `MPCR` (01-MPCR), 3
- `MPCR GEMM` (39-MPCR GEMM), 36
- `MPCR TRSM` (40-MPCR TRSM), 37
- `MPCR.abs` (15-Miscmath), 17
- `MPCR.acos` (22-Trig), 22
- `MPCR.acosh` (23-Hyperbolic), 23
- `MPCR.Add` (04-Arithmetic), 7
- `MPCR.asin` (22-Trig), 22
- `MPCR.asinh` (23-Hyperbolic), 23
- `MPCR.atan` (22-Trig), 22
- `MPCR.atanh` (23-Hyperbolic), 23
- `MPCR.backsolve` (38-Back/Forward solve), 35
- `MPCR.cbind` (10-Bind), 13
- `MPCR.cbind`, Rcpp\_MPCR-method  
(10-Bind), 13
- `MPCR.ceiling` (18-Round), 19
- `MPCR.ChangePrecision`  
(26-Metadata), 25
- `MPCR.ChangePrecision`, Rcpp\_MPCR-method  
(26-Metadata), 25
- `MPCR.chol` (28-Cholesky decomposition), 27
- `MPCR.chol2inv` (29-Cholesky inverse), 27
- `MPCR.Concatenate`  
(09-Concatenate), 12
- `MPCR.Concatenate`, Rcpp\_MPCR-method  
(09-Concatenate), 12
- `MPCR.copy` (08-Copy), 11
- `MPCR.cos` (22-Trig), 22
- `MPCR.cosh` (23-Hyperbolic), 23
- `MPCR.crossprod` (30-Crossprod), 28
- `MPCR.diag` (11-Diagonal), 14
- `MPCR.Divide` (04-Arithmetic), 7
- `MPCR.eigen` (31-Eigen decomposition), 29
- `MPCR.exp` (13-Log), 15
- `MPCR.expm1` (13-Log), 15
- `MPCR.floor` (18-Round), 19
- `MPCR.forwardsolve`  
(38-Back/Forward solve), 35
- `MPCR.gamma` (21-Special Math), 21
- `MPCR.gemm` (39-MPCR GEMM), 36
- `MPCR.gemm`, Rcpp\_MPCR-method  
(39-MPCR GEMM), 36
- `MPCR.is.double` (25-Check precision), 24
- `MPCR.is.double`, Rcpp\_MPCR-method  
(25-Check precision), 24
- `MPCR.is.finite` (14-Mathis), 16
- `MPCR.is.float` (25-Check precision), 24
- `MPCR.is.float`, Rcpp\_MPCR-method  
(25-Check precision), 24
- `MPCR.is.half` (25-Check precision), 24
- `MPCR.is.half`, Rcpp\_MPCR-method  
(25-Check precision), 24
- `MPCR.is.infinite` (14-Mathis), 16
- `MPCR.is.na` (16-NA's), 17
- `MPCR.is.na`, Rcpp\_MPCR-method  
(16-NA's), 17
- `MPCR.is.nan` (14-Mathis), 16
- `MPCR.is.single` (25-Check precision), 24
- `MPCR.is.single`, Rcpp\_MPCR-method  
(25-Check precision), 24
- `MPCR.isSymmetric` (32-Symmetric), 30
- `MPCR.La.svd` (37-Singular value decomposition), 34
- `MPCR.lgamma` (21-Special Math), 21
- `MPCR.log` (13-Log), 15
- `MPCR.log10` (13-Log), 15

- MPCR.log2 (13-Log), 15
- MPCR.max (12-Extremes), 14
- MPCR.min (12-Extremes), 14
- MPCR.Multiply (04-Arithmetic), 7
- MPCR.na.exclude (16-NA's), 17
- MPCR.na.exclude, Rcpp\_MPCR-method (16-NA's), 17
- MPCR.na.omit (16-NA's), 17
- MPCR.na.omit, Rcpp\_MPCR-method (16-NA's), 17
- MPCR.ncol (07-Dimensions), 11
- MPCR.norm (33-Norm), 31
- MPCR.nrow (07-Dimensions), 11
- MPCR.object.size (26-Metadata), 25
- MPCR.object.size, Rcpp\_MPCR-method (26-Metadata), 25
- MPCR.Power (04-Arithmetic), 7
- MPCR.print (27-Print), 26
- MPCR.qr (34-QR decomposition), 31
- MPCR.rbind (10-Bind), 13
- MPCR.rbind, Rcpp\_MPCR-method (10-Bind), 13
- MPCR.rcond (35-Reciprocal condition), 32
- MPCR.rep (17-Replicate), 18
- MPCR.round (18-Round), 19
- MPCR.scale (19-Scale), 20
- MPCR.show (27-Print), 26
- MPCR.sin (22-Trig), 22
- MPCR.sinh (23-Hyperbolic), 23
- MPCR.solve (36-Solve), 33
- MPCR.sqrt (15-Miscmath), 17
- MPCR.storage.mode (26-Metadata), 25
- MPCR.str (27-Print), 26
- MPCR.Subtract (04-Arithmetic), 7
- MPCR.svd (37-Singular value decomposition), 34
- MPCR.sweep (20-Sweep), 20
- MPCR.t (24-Transpose), 24
- MPCR.tan (22-Trig), 22
- MPCR.tanh (23-Hyperbolic), 23
- MPCR.tcrossprod (30-Crossprod), 28
- MPCR.ToNumericMatrix (03-Converters), 6
- MPCR.ToNumericVector (03-Converters), 6
- MPCR.trsm (40-MPCR TRSM), 37
- MPCR.trsm, Rcpp\_MPCR-method (40-MPCR TRSM), 37
- MPCR.trunc (18-Round), 19
- MPCR.typeof (26-Metadata), 25
- MPCR.which.max (12-Extremes), 14
- MPCR.which.min (12-Extremes), 14
- MPCRTile (02-MPCRTile), 4
- MPCRTile Chol (42-MPCRTile POTRF), 39
- MPCRTile GEMM (41-MPCRTile GEMM), 38
- MPCRTile.chol (42-MPCRTile POTRF), 39
- MPCRTile.copy (08-Copy), 11
- MPCRTile.gemm (41-MPCRTile GEMM), 38
- MPCRTile.gemm, Rcpp\_MPCRTile-method (41-MPCRTile GEMM), 38
- MPCRTile.trsm (43-MPCRTile TRSM), 40
- MPCRTile.trsm, Rcpp\_MPCRTile-method (43-MPCRTile TRSM), 40
- NA's (16-NA's), 17
- ncol, Rcpp\_MPCR-method (07-Dimensions), 11
- new, 3, 4
- norm (33-Norm), 31
- norm, Rcpp\_MPCR-method (33-Norm), 31
- nrow, Rcpp\_MPCR-method (07-Dimensions), 11
- print (27-Print), 26
- print, Rcpp\_MPCR-method (27-Print), 26
- qr (34-QR decomposition), 31
- qr, Rcpp\_MPCR-method (34-QR decomposition), 31
- qr.Q, ANY-method (34-QR decomposition), 31
- qr.R, ANY-method (34-QR decomposition), 31
- rcond (35-Reciprocal condition), 32
- rcond, Rcpp\_MPCR-method (35-Reciprocal condition), 32

Rcpp\_MPCR-class (*01-MPCR*), [3](#)  
 Rcpp\_MPCRTile-class  
     (*02-MPCRTile*), [4](#)  
 rep, Rcpp\_MPCR-method  
     (*17-Replicate*), [18](#)  
 replicate (*17-Replicate*), [18](#)  
 round (*18-Round*), [19](#)  
 round, Rcpp\_MPCR-method  
     (*18-Round*), [19](#)  
  
 scale (*19-Scale*), [20](#)  
 scale, Rcpp\_MPCR-method  
     (*19-Scale*), [20](#)  
 show, Rcpp\_MPCR-method (*27-Print*),  
     [26](#)  
 sin, Rcpp\_MPCR-method (*22-Trig*), [22](#)  
 sinh, Rcpp\_MPCR-method  
     (*23-Hyperbolic*), [23](#)  
 solve (*36-Solve*), [33](#)  
 solve, Rcpp\_MPCR-method  
     (*36-Solve*), [33](#)  
 specialmath (*21-Special Math*), [21](#)  
 sqrt, Rcpp\_MPCR-method  
     (*15-Miscmath*), [17](#)  
 storage.mode, Rcpp\_MPCR-method  
     (*26-Metadata*), [25](#)  
 svd (*37-Singular value decomposition*), [34](#)  
 svd, Rcpp\_MPCR-method  
     (*37-Singular value decomposition*), [34](#)  
 sweep (*20-Sweep*), [20](#)  
 sweep, Rcpp\_MPCR-method  
     (*20-Sweep*), [20](#)  
  
 t, Rcpp\_MPCR-method  
     (*24-Transpose*), [24](#)  
 tan, Rcpp\_MPCR-method (*22-Trig*), [22](#)  
 tanh, Rcpp\_MPCR-method  
     (*23-Hyperbolic*), [23](#)  
 tcrossprod, Rcpp\_MPCR-method  
     (*30-Crossprod*), [28](#)  
 transpose (*24-Transpose*), [24](#)  
 trig (*22-Trig*), [22](#)  
 trunc, Rcpp\_MPCR-method  
     (*18-Round*), [19](#)  
 typeof, Rcpp\_MPCR-method  
     (*26-Metadata*), [25](#)  
  
 which.max, Rcpp\_MPCR-method  
     (*12-Extremes*), [14](#)  
 which.min, Rcpp\_MPCR-method  
     (*12-Extremes*), [14](#)