

Using R6causal

Juha Karvanen

2023-11-18

Overview

The R package `R6causal` implements an R6 class called `SCM`. The class aims to simplify working with structural causal models. The missing data mechanism can be defined as a part of the structural model.

The class contains methods for

- defining a structural causal model via functions, text or conditional probability tables
- printing basic information on the model
- plotting the graph for the model using packages `igraph` or `qgraph`
- simulating data from the model
- applying an intervention
- checking the identifiability of a query using the R packages `causaleffect` and `dosearch`
- defining the missing data mechanism
- simulating incomplete data from the model according to the specified missing data mechanism
- checking the identifiability in a missing data problem using the R package `dosearch`
- checking the identifiability of a counterfactual query using the R package `cfid`

In addition, there are functions for

- running experiments
- counterfactual inference using simulation
- evaluating fairness of a prediction model

The class `ParallelWorld` inherits `SCM` and defines a structural causal model that describes parallel worlds for counterfactual inference.

The class `LinearGaussianSCM` inherits `SCM` and defines a structural causal model where all functions are linear and all background variables follow Gaussian distribution.

Setup

```
library(R6causal)
library(data.table)
library(stats)
data.table::setDTthreads(2)
```

Defining the model

Structural causal model (SCM) for a backdoor situation can be defined as follows

```
backdoor <- SCM$new("backdoor",
  uflist = list(
```

```

uz = function(n) {return(runif(n))},
ux = function(n) {return(runif(n))},
uy = function(n) {return(runif(n))}
),
vflist = list(
z = function(uz) {
  return(as.numeric(uz < 0.4))},
x = function(ux, z) {
  return(as.numeric(ux < 0.2 + 0.5*z))},
y = function(uy, z, x) {
  return(as.numeric(uy < 0.1 + 0.4*z + 0.4*x))}

)
)

```

A shortcut notation for this is

```

backdoor_text <- SCM$new("backdoor",
  uflist = list(
    uz = "n : runif(n)",
    ux = "n : runif(n)",
    uy = "n : runif(n)"
  ),
  vflist = list(
    z = "uz : as.numeric(uz < 0.4)",
    x = "ux, z : as.numeric(ux < 0.2 + 0.5*z)",
    y = "uy, z, x : as.numeric(uy < 0.1 + 0.4*z + 0.4*x)"
  )
)
)
```

Alternatively the functions of SCM can be specified via conditional probability tables

```

backdoor_condprob <- SCM$new("backdoor",
  uflist = list(
    uz = function(n) {return(runif(n))},
    ux = function(n) {return(runif(n))},
    uy = function(n) {return(runif(n))}
  ),
  vflist = list(
    z = function(uz) {
      return( generate_condprob( ycondx = data.table(z = c(0,1),
                                                    prob = c(0.6,0.4)),
                                x = data.table(uz = uz),
                                Umerge_expr = "uz"))},
    x = function(ux, z) {
      return( generate_condprob( ycondx = data.table(x = c(0,1,0,1),
                                                    z = c(0,0,1,1),
                                                    prob = c(0.8,0.2,0.3,0.7)),
                                x = data.table(z = z, ux = ux),
                                Umerge_expr = "ux"))},
    y = function(uy, z, x) {
      return( generate_condprob( ycondx = data.table(y= rep(c(0,1), 4),
                                                    z = c(0,0,1,1,0,0,1,1),
                                                    x = c(0,0,0,0,1,1,1,1),
                                                    prob = c(0.9,0.1,0.5,0.5,
                                                        0.5,0.5,0.1,0.9))),
```

```

        x = data.table(z = z, x = x, uy = uy),
        Umerge_expr = "uy"))
    )
)

```

It is possible to mix the styles and define some elements of a function list as functions, some as text and some as conditional probability tables.

Defining a linear Gaussian SCM

A linear Gaussian SCM can be defined giving the coefficients for the structural equations:

```

lgbackdoor <- LinearGaussianSCM$new("Linear Gaussian Backdoor",
                                      linear_gaussian = list(
                                          uflist = list(ux = function(n) {rnorm(n)},
                                                        uy = function(n) {rnorm(n)},
                                                        uz = function(n) {rnorm(n)}),
                                          vnames = c("x", "y", "z"),
                                          vcoefmatrix = matrix(c(0, 0.4, 0, 0, 0, 0, 0.6, 0.8, 0), 3, 3),
                                          ucoefvector = c(1, 1, 1),
                                          ccoefvector = c(0, 0, 0)))
print(lgbackdoor)
#> Name of the model: Linear Gaussian Backdoor
#>
#> Graph:
#> z -> x
#> x -> y
#> z -> y
#>
#> Functions of background (exogenous) variables:
#>
#> $ux
#> function(n) {rnorm(n)}
#>
#> $uy
#> function(n) {rnorm(n)}
#>
#> $uz
#> function(n) {rnorm(n)}
#>
#> Functions of endogenous variables:
#>
#> $x
#> function (z, ux) {
#>   return(0 + 0.6 * z + 1 * ux)
#> }
#> <environment: 0x0000024714f15720>
#>
#> $y
#> function (x, z, uy) {
#>   return(0 + 0.4 * x + 0.8 * z + 1 * uy)
#> }

```

```

#> <environment: 0x0000024714f04910>
#>
#> $z
#> function (uz)
#> {
#>   return(0 + 1 * uz)
#> }
#> <environment: 0x0000024714f07dd0>
#>
#> Topological order of endogenous variables:
#> [1] "z" "x" "y"
#>
#> No missing data mechanism

```

It is also possible to generate the underlying DAG and the coefficients randomly:

```

randomlg <- LinearGaussianSCM$new("Random Linear Gaussian",
                                    random_linear_gaussian = list(
                                      nv = 6,
                                      edgeprob=0.5,
                                      vcoefdistr = function(n) {rnorm(n)},
                                      ccoefdistr = function(n) {rnorm(n)},
                                      ucoefdistr = function(n) {rnorm(n)}))
print(randomlg)
#> Name of the model: Random Linear Gaussian
#>
#> Graph:
#> v1 -> v2
#> v2 -> v4
#> v5 -> v4
#> v1 -> v6
#> v2 -> v6
#> v5 -> v6
#>
#> Functions of background (exogenous) variables:
#>
#> $u1
#> function (n)
#> {
#>   return(rnorm(n))
#> }
#> <environment: 0x00000247186aaf40>
#>
#> $u2
#> function (n)
#> {
#>   return(rnorm(n))
#> }
#> <environment: 0x00000247186b4188>
#>
#> $u3
#> function (n)
#> {
#>   return(rnorm(n))

```

```

#> }
#> <environment: 0x00000247186b1470>
#>
#> $u4
#> function (n)
#> {
#>   return(rnorm(n))
#> }
#> <environment: 0x00000247186ae858>
#>
#> $u5
#> function (n)
#> {
#>   return(rnorm(n))
#> }
#> <environment: 0x00000247186b3b80>
#>
#> $u6
#> function (n)
#> {
#>   return(rnorm(n))
#> }
#> <environment: 0x00000247186befd8>
#>
#> Functions of endogenous variables:
#>
#> $v1
#> function (u1)
#> {
#>   return(-0.874108406310088 + 1.41674293091438 * u1)
#> }
#> <environment: 0x00000247186c1950>
#>
#> $v2
#> function (v1, u2)
#> {
#>   return(0.621408077314456 + 0.877024898333607 * v1 + 0.554819351454142 *
#>         u2)
#> }
#> <environment: 0x00000247186ccc90>
#>
#> $v3
#> function (u3)
#> {
#>   return(-0.144717175501409 + -0.656824690079663 * u3)
#> }
#> <environment: 0x00000247186c3ca8>
#>
#> $v4
#> function (v2, v5, u4)
#> {
#>   return(1.24385329947927 + 0.749819455160944 * v2 + 0.249156721203491 *
#>         v5 + -1.3904985686492 * u4)

```

```

#> }
#> <environment: 0x00000247186d2dd8>
#>
#> $v5
#> function (u5)
#> {
#>   return(-1.11892080931192 + -0.479777443284055 * u5)
#> }
#> <environment: 0x00000247186c7b40>
#>
#> $v6
#> function (v1, v2, v5, u6)
#> {
#>   return(-1.45693866091209 + -0.4811146483387 * v1 + -0.69388664633599 *
#>         v2 + -0.768457818139036 * v5 + 0.923122323068245 * u6)
#> }
#> <environment: 0x00000247186cad60>
#>
#> Topological order of endogenous variables:
#> [1] "v1" "v3" "v5" "v2" "v4" "v6"
#>
#> No missing data mechanism

```

Printing the model


The print method presents the basic information on the model

```
backdoor
#> Name of the model: backdoor
#>
#> Graph:
#> z -> x
#> z -> y
#> x -> y
#>
#> Functions of background (exogenous) variables:
#>
#> $uz
#> function(n) {return(runif(n))}
#>
#> $ux
#> function(n) {return(runif(n))}
#>
#> $uy
#> function(n) {return(runif(n))}
#>
#> Functions of endogenous variables:
#>
#> $z
#> function(uz) {
#>     return(as.numeric(uz < 0.4))
#>
#> $x
#> function(ux, z) {
#>     return(as.numeric(ux < 0.2 + 0.5*z))}
#>
#> $y
#> function(uy, z, x) {
#>     return(as.numeric(uy < 0.1 + 0.4*z + 0.4*x))}
#>
#> Topological order of endogenous variables:
#> [1] "z" "x" "y"
#>
#> No missing data mechanism
```


Plotting the graph

The plotting method of the package `igraph` is used by default. If `qgraph` is available, its plotting method can be used as well. The argument `subset` controls which variables are plotted. Plotting parameters are passed to the plotting method.


```
backdoor$plot(vertex.size = 25) # with package 'igraph'
```



```
backdoor$plot(subset = "v") # only observed variables
```



```
if (requireNamespace("qgraph", quietly = TRUE)) backdoor$plot(method = "qgraph")
```



```
# alternative look with package 'qgraph'
```

Simulating data

Calling method `simulate()` creates or updates data table `simdata`.

```


backdoor$simulate(10)
backdoor$simdata
#>      uz          ux          uy  z  x  y
#> 1: 0.7728560  0.04783734  0.40316817 0 1 1
#> 2: 0.6557514  0.21003555  0.84930382 0 0 0
#> 3: 0.1498437  0.57696786  0.84806126 1 1 1
#> 4: 0.7447288  0.24595002  0.15895769 0 0 0
#> 5: 0.9976432  0.26092262  0.31783183 0 0 0
#> 6: 0.7159726  0.12435491  0.01870671 0 1 1
#> 7: 0.1958957  0.64853166  0.54125387 1 1 1
#> 8: 0.9931485  0.61877967  0.23995472 0 0 0
#> 9: 0.2697301  0.98479715  0.82915003 1 0 0
#> 10: 0.6505578  0.40424012  0.39835067 0 0 0
backdoor$simulate(8)
backdoor$simdata
#>      uz          ux          uy  z  x  y
#> 1: 0.4833479  0.4007874  0.07220994 0 0 1
#> 2: 0.4462248  0.2344714  0.02897326 0 0 1
#> 3: 0.6069826  0.8923524  0.93320993 0 0 0
#> 4: 0.6357160  0.8017341  0.89557624 0 0 0
#> 5: 0.6751718  0.3245823  0.35437712 0 0 0
#> 6: 0.8872067  0.3097941  0.36439379 0 0 0
#> 7: 0.4310017  0.3422076  0.70888860 0 0 0
  
```

```
#> 8: 0.2569434 0.5874797 0.07481673 1 1 1
backdoor_text$simulate(20)
backdoor_condprob$simulate(30)
```

Applying an intervention

In an intervention, the structural equation of the target variable is changed.


```
backdoor_x1 <- backdoor$clone() # making a copy
backdoor_x1$intervene("x", 1) # applying the intervention
backdoor_x1$plot(method = "qgraph") # to see that arrows incoming to x are cut
```



```
backdoor_x1$simulate(10) # simulating from the intervened model
backdoor_x1$simdata
#>          uz          ux          uy  z  x  y
#> 1: 0.62997290 0.3558503 0.9305637 0 1 0
#> 2: 0.72306475 0.8181661 0.9001112 0 1 0
#> 3: 0.84575187 0.6348200 0.2189730 0 1 1
#> 4: 0.87357792 0.7679340 0.7208477 0 1 0
#> 5: 0.93222775 0.8281281 0.1402974 0 1 1
#> 6: 0.70568889 0.2038273 0.5953877 0 1 0
#> 7: 0.15904410 0.1264877 0.7561948 1 1 1
#> 8: 0.94477340 0.7544117 0.1369158 0 1 1
#> 9: 0.73473279 0.5385419 0.5251055 0 1 0
#> 10: 0.09526467 0.4741884 0.2634645 1 1 1
```

An intervention can redefine a structural equation

```
backdoor_yz <- backdoor$clone() # making a copy
backdoor_yz$intervene("y",
  function(uy, z) {return(as.numeric(uy < 0.1 + 0.8*z ))}) # making y a function of z only
backdoor_yz$plot(method = "qgraph") # to see that arrow x -> y is cut
```



Running an experiment (set of interventions)

The function `run_experiment` applies a set of interventions, simulates data and collects the results.

```
backdoor_experiment <- run_experiment(backdoor,
                                         intervene = list(x = c(0,1)),
                                         response = "y",
                                         n = 10000)

str(backdoor_experiment)
#> List of 2
#> $ interventions:Classes 'data.table' and 'data.frame': 2 obs. of 1 variable:
#> ..$ x: num [1:2] 0 1
#> ...- attr(*, ".internal.selfref")=<externalptr>
#> ...- attr(*, "sorted")= chr "x"
#> $ response_list:List of 1
#> ..$ y:Classes 'data.table' and 'data.frame': 10000 obs. of 2 variables:
#> ... ..$ V1: num [1:10000] 0 0 1 0 0 1 0 0 1 0 ...
#> ... ..$ V2: num [1:10000] 1 1 0 1 1 0 1 0 1 1 ...
#> ... ...- attr(*, ".internal.selfref")=<externalptr>
colMeans(backdoor_experiment$response_list$y)
#>      V1      V2
#> 0.2574 0.6491
```

Applying the ID algorithm, Do-search and cfid

There are direct plugins to R packages `causaleffect`, `dosearch` and `cfid` that can be used to solve identifiability problems.

```
backdoor$causal.effect(y = "y", x = "x")
#> [1] "\sum_z P(y|z,x)P(z)"
backdoor$dosearch(data = "p(x,y,z)", query = "p(y|do(x))")
#> \sum_z\left(p(z)p(y|x,z)\right)
backdoor$cfid(gamma = cfid::conj(cfid::cf("Y",0), cfid::cf("X",0, c(Z=1))) )
#> The query P(y /\ x_{z'}) is not identifiable from P_*
```

Counterfactual inference (a simple case)

Let us assume that intervention $do(X=0)$ was applied and the response $Y = 0$ was recorded. What is the probability that in this situation the intervention $do(X=1)$ would have led to the response $Y = 1$? We estimate this probability by means of simulation.

```
cfdata <- counterfactual(backdoor, situation = list(do = list(target = "x", ifunction = 0),
                                                    condition = data.table( x = 0, y = 0)),
                           target = "x", ifunction = 1, n = 100000,
                           control = list(method = "rejection"))

mean(cfdata$y)
#> [1] 0.53761
```

The result differs from $P(Y = 1 | do(X = 1))$

```
backdoor_x1$simulate(100000)
mean(backdoor_x1$simdata$y)
#> [1] 0.6587
```

Counterfactual inference (parallel worlds)

Parallel world graphs (a generalization of a twin graph) are used for counterfactual inference with several counterfactual interventions . The package implements class `ParallelWorld` which heritates class `SCM`. A `ParallelWorld` object is created from an `SCM` object by specifying the interventions for each world. By default the variables of the parallel worlds are named with suffixes “`_1`”, “`_2`”, ...”

In the example below, we have the original world (variables `x`, `z`, `y`) and its two variants. In the variant 1 (variables `x_1`, `z_1`, `y_1`), the value of `x` (variable `x_1` in the object) is set to be 0. In the variant 2 (variables `x_2`, `z_2`, `y_2`), the value of `x` (variable `x_2` in the object) is set to be 0 and the value of `z` (variable `z_2` in the object) is set to be 1.

```
backdoor_parallel <- ParallelWorld$new(
  backdoor,
  dolist=list(
    list(target = "x",
         ifunction = 0),
    list(target = list("z", "x"),
         ifunction = list(1,0)))
  )
)
backdoor_parallel
#> Name of the model: backdoor
#>
```

```

#> Graph:
#> uz -> z
#> z -> x
#> uy -> y
#> z -> y
#> x -> y
#> uz -> z_1
#> uy -> y_1
#> z_1 -> y_1
#> x_1 -> y_1
#> uy -> y_2
#> z_2 -> y_2
#> x_2 -> y_2
#>
#> Functions of background (exogenous) variables:
#>
#> $uz
#> function(n) {return(runif(n))}
#> <bytecode: 0x0000024729eee5b8>
#>
#> $ux
#> function(n) {return(runif(n))}
#> <bytecode: 0x0000024729f84d80>
#>
#> $uy
#> function(n) {return(runif(n))}
#> <bytecode: 0x000002472a01d358>
#>
#> Functions of endogenous variables:
#>
#> $z
#> function(uz) {
#>     return(as.numeric(uz < 0.4))
#> <bytecode: 0x000002472a0d5150>
#>
#> $x
#> function(ux, z) {
#>     return(as.numeric(ux < 0.2 + 0.5*z))
#> <bytecode: 0x000002472a251d90>
#>
#> $y
#> function(uy, z, x) {
#>     return(as.numeric(uy < 0.1 + 0.4*z + 0.4*x))
#> <bytecode: 0x000002472a3c6338>
#>
#> $z_1
#> function (uz)
#> {
#>     return(as.numeric(uz < 0.4))
#> }
#>
#> $x_1
#> function (...)
```


```

#> {
#>   return(constant)
#> }
#> <environment: 0x0000024729e56d30>
#>
#> $y_1
#> function (uy, z_1, x_1)
#> {
#>   return(as.numeric(uy < 0.1 + 0.4 * z_1 + 0.4 * x_1))
#> }
#>
#> $z_2
#> function (...)

#> {
#>   return(constant)
#> }
#> <environment: 0x0000024727fc3458>
#>
#> $x_2
#> function (...)

#> {
#>   return(constant)
#> }
#> <environment: 0x0000024727fce858>
#>
#> $y_2
#> function (uy, z_2, x_2)
#> {
#>   return(as.numeric(uy < 0.1 + 0.4 * z_2 + 0.4 * x_2))
#> }
#>
#> Topological order of endogenous variables:
#> [1] "x_1" "z_2" "x_2" "z"    "z_1" "y_2" "x"    "y_1" "y"
#>
#> No missing data mechanism
if (requireNamespace("qgraph", quietly = TRUE)) backdoor_parallel$plot(method = "qgraph")

```



Counterfactual data can be simulated with function `counterfactual`. In the example below, we know that variable y obtained value 0 in the original world as well as variants 1 and 2. We are interested in the counterfactual distribution of y if x had been set to 1.

```
cfdata <- counterfactual(backdoor_parallel,
                           situation = list(
                               do = NULL,
                               condition = data.table::data.table( y = 0, y_1 = 0, y_2 = 0),
                               target = "x",
                               ifunction = 1,
                               n = 100000,
                               control = list(method = "rejection"))

mean(cfdata$y)
#> [1] 0.12277
```

The printed value is a simulation based estimate for the counterfactual probability $P(Y = 1)$.

An alternative way for answering the same question defines the case of interest as one of the parallel worlds (here variant 3).

```
backdoor_parallel2 <- ParallelWorld$new(
  backdoor,
  dolist=list(
    list(target = "x",
         ifunction = 0),
    list(target = list("z", "x"),
         ifunction = list(1,0)),
    list(target = "x",
         ifunction = 1)
  )
)
```

```

cfdata <- counterfactual(backdoor_parallel2,
                           situation = list(
                               do = NULL,
                               condition = data.table::data.table( y = 0, y_1 = 0, y_2 = 0)),
                           n = 100000,
                           control = list(method = "rejection"))

mean(cfdata$y_3)
#> [1] 0.12314

```

The printed value is a simulation based estimate for the counterfactual probability $P(Y = 1)$.

A model with a missing data mechanism

The missing data mechanism is defined in similar manner as the other variables.


```

backdoor_md <- SCM$new("backdoor_md",
                        uflist = list(
                            uz = "n : runif(n)",
                            ux = "n : runif(n)",
                            uy = "n : runif(n)",
                            urz = "n : runif(n)",
                            urx = "n : runif(n)",
                            ury = "n : runif(n)"
                        ),
                        vflist = list(
                            z = "uz : as.numeric(uz < 0.4)",
                            x = "ux, z : as.numeric(ux < 0.2 + 0.5*z)",
                            y = "uy, z, x : as.numeric(uy < 0.1 + 0.4*z + 0.4*x)"
                        ),
                        rflist = list(
                            z = "urz : as.numeric(urz < 0.9)",
                            x = "urx, z : as.numeric((urx + z)/2 < 0.9)",
                            y = "ury, z : as.numeric((ury + z)/2 < 0.9)"
                        ),
                        rprefix = "r_"
)


```

Plotting the graph for a model with missing data mechanism

```
backdoor_md$plot(vertex.size = 25, edge.arrow.size=0.5) # with package 'igraph'
```



```
backdoor_md$plot(subset = "v") # only observed variables a
```



```
if (!requireNamespace("qgraph", quietly = TRUE)) backdoor_md$plot(method = "qgraph")
# alternative look with package 'qgraph'
```

Simulating incomplete data

By default both complete data and incomplete data are simulated. The incomplete dataset is named as `$simdata_obs`.

```
backdoor_md$simulate(100)
summary(backdoor_md$simdata)
#>      uz          ux          uy          urz
#> Min. :0.0009881  Min. :0.006888  Min. :0.006665  Min. :0.0249
#> 1st Qu.:0.2005260  1st Qu.:0.253816  1st Qu.:0.194837  1st Qu.:0.2308
#> Median :0.4625494  Median :0.512815  Median :0.478325  Median :0.4764
#> Mean   :0.4708455  Mean   :0.487967  Mean   :0.488647  Mean   :0.4880
#> 3rd Qu.:0.7123149  3rd Qu.:0.720430  3rd Qu.:0.741221  3rd Qu.:0.7114
#> Max.   :0.9930208  Max.   :0.993450  Max.   :0.998812  Max.   :0.9965
#>
#>      urx          ury          z           x
#> Min. :0.01912  Min. :0.01456  Min. :0.00  Min. :0.00
#> 1st Qu.:0.25383  1st Qu.:0.31613  1st Qu.:0.00  1st Qu.:0.00
```

```

#> Median :0.49155  Median :0.49779  Median :0.00  Median :0.00
#> Mean   :0.50928  Mean   :0.49643  Mean   :0.46  Mean   :0.44
#> 3rd Qu.:0.79531  3rd Qu.:0.70900  3rd Qu.:1.00  3rd Qu.:1.00
#> Max.   :0.98021  Max.   :0.97863  Max.   :1.00  Max.   :1.00
#>
#>      y          z_md        x_md        y_md
#> Min.  :0.00  Min.  :0.0000  Min.  :0.0000  Min.  :0.0000
#> 1st Qu.:0.00  1st Qu.:0.0000  1st Qu.:0.0000  1st Qu.:0.0000
#> Median :0.00  Median :0.0000  Median :0.0000  Median :0.0000
#> Mean   :0.46  Mean   :0.4725  Mean   :0.4432  Mean   :0.4409
#> 3rd Qu.:1.00  3rd Qu.:1.0000  3rd Qu.:1.0000  3rd Qu.:1.0000
#> Max.   :1.00  Max.   :1.0000  Max.   :1.0000  Max.   :1.0000
#> NA's   :9     NA's   :12     NA's   :7
#>      r_z        r_x        r_y
#> Min.  :0.00  Min.  :0.00  Min.  :0.00
#> 1st Qu.:1.00 1st Qu.:1.00 1st Qu.:1.00
#> Median :1.00  Median :1.00  Median :1.00
#> Mean   :0.91  Mean   :0.88  Mean   :0.93
#> 3rd Qu.:1.00 3rd Qu.:1.00 3rd Qu.:1.00
#> Max.   :1.00  Max.   :1.00  Max.   :1.00
#>
#> summary(backdoor_md$simdata_obs)
#>      z_md        x_md        y_md        r_z
#> Min.  :0.0000  Min.  :0.0000  Min.  :0.0000  Min.  :0.00
#> 1st Qu.:0.0000 1st Qu.:0.0000 1st Qu.:0.0000 1st Qu.:1.00
#> Median :0.0000  Median :0.0000  Median :0.0000  Median :1.00
#> Mean   :0.4725  Mean   :0.4432  Mean   :0.4409  Mean   :0.91
#> 3rd Qu.:1.0000 3rd Qu.:1.0000 3rd Qu.:1.0000 3rd Qu.:1.00
#> Max.   :1.0000  Max.   :1.0000  Max.   :1.0000  Max.   :1.00
#> NA's   :9     NA's   :12     NA's   :7
#>      r_x        r_y
#> Min.  :0.00  Min.  :0.00
#> 1st Qu.:1.00 1st Qu.:1.00
#> Median :1.00  Median :1.00
#> Mean   :0.88  Mean   :0.93
#> 3rd Qu.:1.00 3rd Qu.:1.00
#> Max.   :1.00  Max.   :1.00
#>

```

By using the argument `fixedvars` one can keep the complete data unchanged and re-simulate the missing data mechanism.

```

backdoor_md$simulate(100, fixedvars = c("x", "y", "z", "ux", "uy", "uz"))
summary(backdoor_md$simdata)
#>      uz        ux        uy        urz
#> Min.  :0.0009881  Min.  :0.006888  Min.  :0.006665  Min.  :0.006917
#> 1st Qu.:0.2005260  1st Qu.:0.253816  1st Qu.:0.194837  1st Qu.:0.222695
#> Median :0.4625494  Median :0.512815  Median :0.478325  Median :0.429692
#> Mean   :0.4708455  Mean   :0.487967  Mean   :0.488647  Mean   :0.449283
#> 3rd Qu.:0.7123149  3rd Qu.:0.720430  3rd Qu.:0.741221  3rd Qu.:0.628679
#> Max.   :0.9930208  Max.   :0.993450  Max.   :0.998812  Max.   :0.995040
#>
#>      urx        ury        z         x
#> Min.  :0.002533  Min.  :0.009308  Min.  :0.00  Min.  :0.00

```

```

#> 1st Qu.:0.176621   1st Qu.:0.208492   1st Qu.:0.00   1st Qu.:0.00
#> Median :0.462471   Median :0.544313   Median :0.00   Median :0.00
#> Mean   :0.440669   Mean   :0.516955   Mean   :0.46   Mean   :0.44
#> 3rd Qu.:0.628319   3rd Qu.:0.786014   3rd Qu.:1.00   3rd Qu.:1.00
#> Max.   :0.994485   Max.   :0.992411   Max.   :1.00   Max.   :1.00
#>
#>      y          z_md        x_md        y_md
#> Min.   :0.00   Min.   :0.0000   Min.   :0.0000   Min.   :0.0000
#> 1st Qu.:0.00   1st Qu.:0.0000   1st Qu.:0.0000   1st Qu.:0.0000
#> Median :0.00   Median :0.0000   Median :0.0000   Median :0.0000
#> Mean   :0.46   Mean   :0.4681   Mean   :0.4239   Mean   :0.4318
#> 3rd Qu.:1.00   3rd Qu.:1.0000   3rd Qu.:1.0000   3rd Qu.:1.0000
#> Max.   :1.00   Max.   :1.0000   Max.   :1.0000   Max.   :1.0000
#>           NA's   :6           NA's   :8           NA's   :12
#>
#>      r_z        r_x        r_y
#> Min.   :0.00   Min.   :0.00   Min.   :0.00
#> 1st Qu.:1.00   1st Qu.:1.00   1st Qu.:1.00
#> Median :1.00   Median :1.00   Median :1.00
#> Mean   :0.94   Mean   :0.92   Mean   :0.88
#> 3rd Qu.:1.00   3rd Qu.:1.00   3rd Qu.:1.00
#> Max.   :1.00   Max.   :1.00   Max.   :1.00
#>
#> summary(backdoor_md$simdata_obs)
#>      z_md        x_md        y_md        r_z
#> Min.   :0.0000   Min.   :0.0000   Min.   :0.0000   Min.   :0.00
#> 1st Qu.:0.0000   1st Qu.:0.0000   1st Qu.:0.0000   1st Qu.:1.00
#> Median :0.0000   Median :0.0000   Median :0.0000   Median :1.00
#> Mean   :0.4681   Mean   :0.4239   Mean   :0.4318   Mean   :0.94
#> 3rd Qu.:1.0000   3rd Qu.:1.0000   3rd Qu.:1.0000   3rd Qu.:1.00
#> Max.   :1.0000   Max.   :1.0000   Max.   :1.0000   Max.   :1.00
#> NA's   :6           NA's   :8           NA's   :12
#>
#>      r_x        r_y
#> Min.   :0.00   Min.   :0.00
#> 1st Qu.:1.00   1st Qu.:1.00
#> Median :1.00   Median :1.00
#> Mean   :0.92   Mean   :0.88
#> 3rd Qu.:1.00   3rd Qu.:1.00
#> Max.   :1.00   Max.   :1.00
#>
#>
```

Applying Do-search to a missing data problem

```

backdoor_md$dosearch(data = "p(x*,y*,z*,r_x,r_y,r_z)", query = "p(y|do(x))")
#> \sum_{z}\left(\frac{p(z,r_z=1)}{p(r_z=1)}\right)p(y/z,r_z=1,x,r_x=1,r_y=1)\right)

```

It is automatically recognized that the problem is a missing data problem when `rlist != NULL`.