

The `I3pdfmanagement` module

Managing central PDF resources

L^AT_EX PDF management testphase bundle

The L^AT_EX Project*

Version 0.96a, released 2023-10-09

1 `I3pdfmanagement` documentation

When creating a pdf a number of objects, dictionaries and entries to central “core” dictionaries must be created.

The commands in this module offer interfaces to this core PDF dictionaries. They unify a number of primitives like the pdftex registers and commands `\pdfcatalog`, `\pdfpageattr`, `\pdfpagesattr`, `\pdfinfo`, `\pdfpageresources` and similar commands of the other backends in a backend independant way.

The supported backends are pdflatex, lualatex, (x)dvipdfmx (latex, xelatex and—starting in texlive 2021—lualatex) and dvips with ps2pdf (not completely yet). dvips with distiller could work too but is untested.

That the interfaces are backend independent doesn’t mean that the results and even the compilation behavior is identical. The backends are too different to allow this. Some backends expand arguments e.g. in a `\special` while other don’t. Some backends can insert a resource at the first compilation, while another uses the aux-file and a label and so needs at least two. Some backends create and manage resources automatically which must be managed manually by other backends.

The dictionaries and resources handled by this module are inserted only once in a PDF or only once per page. Examples are the Catalog dictionary, the Info dictionary, the page resources. For these dictionaries and resources management by the L^AT_EX kernel is necessary to avoid that packages overwrite settings from other packages which would lead to clashes and incompatibilities. It is therefore necessary that *all* packages which want to add content to these dictionaries and resources use the interface provided by this module.

As these dictionaries and resources are so central for the PDF format values to these dictionaries are always added globally. Through the interface values can be added (and in many cases also removed) by users and packages, but the actually writing of the dictionary entries and resources to the PDF is handled by the kernel code.

The interface uses as main name to address the resources *Paths* which follow the names and structure described in the PDF reference. This should make it easy to identify the names needed to insert a specific PDF resources with the new interfaces. All *Paths* have names starting with an uppercase letter.

*E-mail: latex-team@latex-project.org

The following tabular summarize the *Paths* and which pdftex primitive they replace:

Info	\pdfinfo
Catalog & various subdictionaries	\pdfcatalog
Pages	\pdfpagesattr
Page, ThisPage	\pdfpageattr
Page/Resources/ExtGState	\pdfpageresources
Page/Resources/Shading	\pdfpageresources
Page/Resources/Pattern	\pdfpageresources
Page/Resources/ColorSpace	\pdfpageresources

There is no *Page/Resources/Properties* dictionary in the list, because this dictionary is not filled directly, but managed through side effects when setting BDC-marks.

1.1 User Commands

To avoid problems with older documents the resource management of this module is not activated unconditionally. The values are pushed out to the dictionaries only if a boolean has been set to true. The state can be tested with a conditional.

```
\pdfmanagement_if_active_p: *
```

New: 2020-07-04

This conditional tests if the resource management code is active.

```
\IfPDFManagementActiveTF This is a LaTeX2e version of the conditional
```

New: 2021-07-23

```
\pdfmanagement_add:nnn          \pdfmanagement_add:nnn {\langle resource path\rangle} {\langle name\rangle} {\langle value\rangle}
\pdfmanagement_add:(nnx|nxx|xxx)
\PDFManagementAdd
```

New: 2020-04-06

Updated: 2021-07-23

This function puts $\{\langle name\rangle\} \{\langle value\rangle\}$ in the PDF resource described by the symbolic name $\{\langle resource path\rangle\}$. Technically it stores it globally in an internal property lists and writes it later into the right PDF dictionary¹. Which values for $\{\langle resource path\rangle\}$ exist is described in the following. $\{\langle name\rangle\}$ should be a PDF Name without the starting slash. Like with all keys used in PDF dictionaries (see the l3pdffdict module) the name is escaped with `\str_convert_pdfname:n` when stored. $\{\langle value\rangle\}$ should be a valid PDF value for this Name in the target dictionary. `\PDFManagementAdd` is a copy of `\pdfmanagement_add:xxx` and so expands all its arguments.

The code works with all major engines but not necessarily in the same way. Most importantly

- The expansion behaviour of the backends can differ. Some backends expand a value always fully when writing to the PDF, with other backends command names could end as strings in the PDF. So one should neither rely on $\{\langle name\rangle\} \{\langle value\rangle\}$ to be expanded nor not expanded by the backend commands.
- The number of compilations needed can differ between the engines and backends. Some engines have to use labels and the aux-file to setup the dictionaries and so need at least two compilations to put everything in place.
- dvips doesn't support everything. It is for example not possible to add manually or through side effects a name tree like /AP or /JavaScript, pdfmark doesn't provide a handler here—at least I didn't find anything suitable.

```
\pdfmanagement_show:n \pdfmanagement_show:n {\langle resource path\rangle}
```

New: 2020-04-08 This shows the content of the dictionary targetted by $\{\langle resource path\rangle\}$ in the log and on the terminal if possible.

It is not reliable for page resources as these are filled at shipout.

It also doesn't show necessarily all the content. For example most backends add automatically entries to the Info dictionary.

```
\pdfmanagement_remove:nn \pdfmanagement_remove:nn {\langle resource path\rangle} {\langle name\rangle}
```

New: 2020-04-07 Removes $/\langle name\rangle$ and its associated $\langle value\rangle$ from the dictionary described with $\{\langle resource path\rangle\}$. The removal is global. If $\langle name\rangle$ is not found no change occurs, i.e there is no need to test for the existence of a name before trying to remove it. Values from the special Catalog entries where the values are collected in arrays can't be removed (but should ever a use case appear it could be added).

¹Currently all resources are PDF dictionaries, so resource and dictionary mean the same.

1.2 Description of the resource pathes

1.2.1 Info: The Info dictionary

- ⌚ If the primitive commands of the engines are used too there will be double entries in the pdf (at least with the backend pdftex and luatex). How pdf viewer handles this is unpredictable.

```
pdfmanagement: Info \pdfmanagement_add:nnn {Info} {\{name\}} {\{value\}}
```

Adds `/<name>` and the `<value>` to the Info dictionary. `<name>` should be a PDF name without the leading slash. Like with all keys used in PDF dictionaries (see the l3pdffdict module) the name is escaped with `\str_convert_pdfname:n` when stored. `<value>` should be a valid pdf value. Any escaping or (re)encoding must be done explicitly. If a `<name>` is used twice, only the last `<value>` set will be used. The Info dictionary is written at the end of the compilation, so values can be set at any time. The Info dictionary expects utf16be in the strings, so a conversion like this is normally sensible:

```
\str_set_convert:Nnnn \l_tmpa_str { Grüße }{\ default } {utf16/string}
\pdfmanagement_add:nnx {Info} {\Title}{(\l_tmpa_str)}
```

The entries in Info dictionary are rather special as the engines/backends adds some core entries, and changing or removing these entries is not always possible.

The special entries are

Producer Added by all engines and backends. Removing the entry is only possible with luatex with `\pdfvariable_suppressooptionalinfo_128`. Changing is possible with `\pdfmanagement_add:nnn` with the exception of dvips/pstopdf where the entry is always something like `GPL_Ghostscript_9.53.3`.

Creator Added by all engines and backends. Removal only possible in luatex by adding 16 to the bitset. Changing is possible with the management command.

CreationDate Added by all engines and backends. With the exception of dvips/ps2pdf `SOURCE_DATE_EPOCH` is honored. With pdftex it is possible to suppress it with `\pdfinfoomitdate_=1`, and in luatex by adding 32 to the bitset. Changing is possible with the management command and will overwrite an epoch setting.

ModDate Added by all engines and backends with the exception of xdvipdfmx. With the exception of dvips/ps2pdf `SOURCE_DATE_EPOCH` is honored. Suppressing it is possible in pdftex with `\pdfinfoomitdate_=1`, and in luatex by adding 64 to the bitset. Changing is possible with the management command.

Trapped Added by pdftex and luatex. Removal only possible in luatex by adding 256 to the bitset. Changing (and adding in the other backends) is possible with the management command.

PTEX.Fullbanner Added by pdftex and luatex. Removal possible in pdftex with `\pdfsuppressptexinfo-1`, in luatex by adding 512 to the bitset. Changing is not possible.

Title Added by dvips/ps2pdf and set to `filename.dvi`. Removal is probably not possible, but it can be overwritten with the management command.

1.2.2 Pages: The “Pages” dictionary



As the content of this dictionary is written at the end it will in pdftex and luatex overwrite values added with the primitive commands (e.g. `\pdfpagesattr`). Package authors should use the management commands instead.

By using this path with the pdfmanagement interface, values can be added to the `/Pages` object. This replaces for example `\pdfpagesattr`.

`pdfmanagement: Pages \pdfmanagement_add:nnn {Pages} {\langle name\rangle} {\langle value\rangle}`

Adds `/\langle name\rangle {\langle value\rangle}` to the `/Pages` dictionary. It is always stored globally. The content is written to the pdf at the end of the compilation, so values can be added, changed or removed until then. `\langle name\rangle` should be a valid pdf name without the leading slash, `\langle value\rangle` should be a valid pdf value. Any escaping or (re)encoding must be done explicitly. Some backends expand the value but this should not be relied on. If a `\langle name\rangle` is used twice, only the last `\langle value\rangle` set will be used.

1.2.3 “Page” and “ThisPage”

`pdfmanagement: Page \pdfmanagement_add:nnn {Page} {\langle name\rangle} {\langle value\rangle}`

New: 2020-04-12

Values added with the path `Page` are added to the page dictionary of the current page and the following pages. The current page means the page on which the command is *executed*. `\langle name\rangle` should be a valid pdf name without the leading slash. Typical names used here are e.g. `Rotate` and `CropBox`. `\langle value\rangle` should be a valid pdf value. Any escaping or (re)encoding must be done explicitly. Some backends expand the value but this should not be relied on. To avoid problems with the asynchronous page breaking the command should be used after `\newpage` or in the header. It should not be used in a float, as it will then quite probably be executed on the wrong page. The value is assigned directly and is always stored globally. If a `\langle name\rangle` is used twice, only the last `\langle value\rangle` set will be used. Names set with `\pdfmanagement_add:nnn{ThisPage}` will overwrite names set with `\pdfmanagement_add:nnn{Page}` if there is a clash. Values can be removed again with `\pdfmanagement_remove:nn`. This replaces `\pdfpageattr`.

`pdfmanagement: ThisPage \pdfmanagement_add:nnn {ThisPage} {\langle name\rangle} {\langle value\rangle}`

New: 2020-04-12

Adds `/\langle name\rangle {\langle value\rangle}` at *shipout* to the page dictionary of the current page. Current page means here the *shipout* page. It is always stored globally. If `\{\langle name\rangle\}` has already a value set in the `Page` dictionary it will be overwritten for this page. `\langle name\rangle` should be a valid pdf name without the leading slash, `\langle value\rangle` should be a valid pdf value. Any escaping or (re)encoding must be done explicitly. If a `\langle name\rangle` is used twice, only the last `\langle value\rangle` set will be used. With the engine pdflatex (at least) a second compilation is needed. Values added to `ThisPage` can not be removed. It is not possible to show the content of this dictionary with `\pdfmanagement_show:n`.

Changing the `/MediaBox` : It is possible to change the `/MediaBox` of one or more pages by setting it for the `Page` or `ThisPage` path (using `Pages` doesn't work, the engines overwrite this)—this works even with dvips and allows to create pages of different sizes. But you must be careful with the values. If you set e.g. with pdflatex `\pdfpageheight` to 300bp you get a mediabox of 0_U_0_U_595_U_300, but pdflatex measure from the top and will also move the reference point up, so effectively you get the *upper* third of the page.

If you set the `/MediaBox` to `0 0 595 300` with `\pdfmanagement_add:nnn` you get the *lower* third. In general it is better to use only the primitive commands to avoid confusing results.

1.2.4 “Page/Resources”: ExtGState, ColorSpace, Shading, Pattern

```
pdfmanagement: Page/Resources/ExtGState \pdfmanagement_add:nnn {Page/Resources/⟨resource⟩} {⟨name⟩}
pdfmanagement: Page/Resources/ColorSpace {⟨value⟩}
pdfmanagement: Page/Resources/Shading
pdfmanagement: Page/Resources/Pattern
```

Updated: 2020-04-10

Adds `/⟨name⟩ ⟨value⟩` to the page resource `⟨resource⟩`. `⟨resource⟩` can be **ExtGState**, **ColorSpace**, **Pattern** oder **Shading**. The values are always stored globally. The content is written to the pdf at the end of the compilation, so values can be added until then. `⟨name⟩` should be a valid pdf name without the leading slash, `⟨value⟩` should be a valid pdf value for the resource. Any escaping or (re)encoding must be done explicitly. If a `⟨name⟩` is used twice, only the last `⟨value⟩` set will be used.

With the dvips backend the command does nothing: these resources are managed by ghostscript or the distiller if e.g. transparency is used.

The resources are added to all pages starting with the first where something has been added to a resources. That means that for example all ExtGState resources are combined in one dictionary object and every page with a ExtGState resource refer to this object ².

 The primitive commands (e.g. `\pdfpageresources`) to set the resources should not be used together with this code as the calls will overwrite each other and values will be lost. This means that currently there are clashes with the packages tikz, transparent and colorspace.

1.2.5 “Catalog” & subdirectories

The catalog is a central dictionary in a PDF with a number of subdictionaries. Entries to the top level of the catalog can be added with `\pdfmanagement_add:nnn\{Catalog\}\{⟨Name⟩\}\{⟨Value⟩\}`. Entries to subdictionaries by using in the first argument one of the pathes described later. The entries in the catalog have varying requirements regarding the PDF management. Some entries (like `/Lang`) are simple values where new values should overwrite existing values, other like for example `/OutputIntents` can contain a number of values and can be filled from more than one source. In some cases the values that needs to be added are not at the top-level but in some subsubdictionary or are actually part of an array. To handle the pdf management uses a variety of internal, special handlers.

 In some cases entries are added implicitly. For example entries to the name tree of the `/EmbeddedFiles` key in the `/Names` directory are added with the commands of the `l3pdffile` module. This clashes with e.g. the embedfile package which should not be used!

²This is similar to how pgf handles this resources

Entries at the top level of the catalog The Names in the following tabular are entries that are added to the top level of the catalog.

If $\langle Name \rangle$ gets assigned a value more than once the last one wins. There is no check that the values have the correct type and format. It is up to the user to ensure that the value does what is intended.

The required PDF version is only mentioned if it is larger than 1.5.

Example: \pdfmanagement_add:nnn_{Catalog}{PageMode}{/UseNone}

Name	Value	Remark
Collection	objref or dict	the content should be build by external packages (see eg embedfile)
DPartRoot	objref or dict	PDF 2.0
Lang	string	e.g. (de-DE)
Legal	objref or dict	
Metadata	objref or stream	
NeedsRendering	boolean	PDF 1.7
OpenAction	array (dest) or dict (action)	
PageLabels	objref or dict	number tree
PageLayout	name	one of /SinglePage, /OneColumn, /TwoColumnLeft, /TwoColumnRight, /TwoPageLeft, /TwoPageRight
PageMode	name	one of /UseNone, /UseOutlines, /UseThumbs, /UseOC, /UseAttachments (PDF 1.6)
Perms	objref or dict	permissions
PieceInfo	objref or dict	
SpiderInfo	objref or dict	
StructTreeRoot	objref or dict	
Threads	objref to an array	
URI	objref or dict	
Version	name	eg. /1.7
<i>(unknown)</i>		an unknown $\langle name \rangle$ will be inserted without a warning.

Simple entries in subdictionaries of the catalog The following resource pathes have been predeclared and allow to add values to the respective subdictionaries of the catalog. The names of the dictionaries follow the naming and location of the dictionaries in the PDF reference. If $\langle Name \rangle$ gets assigned two values the last one wins.

Example: \pdfmanagement_add:nnn_{Catalog/MarkInfo}{Marked}{true}

Path/dictionary	Names	Value	Remark
Catalog/AA	WC, WS, DS, WP, DP	all dict	
Catalog/AcroForm	NeedAppearances	boolean	In pdf 2.0 NeedAppearances is deprecated, it is then required that every widget has an appearance streams.
Catalog/AcroForm/DR	SigFlags DA Q XFA <name>	Integer String Integer stream or array	pdf 1.5 probably unneeded
Catalog/AcroForm/DR/Font	<name>	dict	
Catalog/MarkInfo	Marked UserProperties Suspects	boolean boolean boolean	
Catalog/ViewerPreferences	HideToolbar Direction ...	boolean /R2L or /L2R	many more, see the reference

Catalog entries with multiple values in arrays The following entries are special: Their values are arrays and it must be possible to append to such arrays. This means that a new call to set this value doesn't replace the value but appends it. The value is an object reference. It is sensible to declare the object first. E.g.

```
\pdf_object_new:n      {module/intent}
\pdf_object_write:nnn {module/intent}{dict}{...}
\pdfmanagement_add:nnx {Catalog} {OutputIntents}{\pdf_object_ref:n {module/intent}}
or
\pdf_object_unnamed_write:nn  {dict} { ... }
\pdfmanagement_add:nnx {Catalog} {OutputIntents}{\pdf_object_ref_last:}
```

Path/dictionary	Name	Value	Remark
Catalog/AcroForm	Fields	object reference	
Catalog/AcroForm	CO	object reference	
Catalog	AF	object reference	PDF 2.0, associated files
Catalog/OCProperties	OCGs	object reference	if there are OCProperties, OCGs and D are required.
Catalog/OCProperties	Configs	object reference	
Catalog/OCProperties	D	object reference	This is actually a single value as there can be only one default. If the value is set twice, the second wins, and the first is added to OCProperties/Configs.
Catalog	OutputIntents	object reference	PDF 1.7
Catalog	Requirements	object reference	
Catalog/Names	EmbeddedFiles	object reference	This should reference a filespec dictionary. It will attach the file to the file panel.

Catalog entries for name trees *Not supported in the dvips backend, pdfmark doesn't have an interface here.*

In various places the PDF format allows to reference objects by name instead of by object reference. The relationship between a name and the object reference are stored in so-called *name trees*, which are stored in the Catalog/Names dictionary. The /Dests and the /EmbeddedFiles name trees are handled implicitly if destinations or files are added. Names to the other name trees can be added with \pdfmanagement_add:nnn, e.g. to add an value to the AP names (for appearance streams) use

```
\pdfmanagement_add:nnx { Catalog / Names / AP } {myAPname} {\pdf_object_ref_last:}
```

Remarks:

- The name `myAPname` is processed through `\pdf_string_from_unicode:nnN{utf8/string}` and parentheses are added automatically. Ensure that the use of the name handles it in the same way.
- It is currently not possible to test if a name has already been used by another package or previous code, so use names where you can be confident that they are unique. (It would be possible to split up the first part and test, but it would slow down the compilation and I'm not sure if it is worth the trouble)
- The value is not preprocessed, it is up-to-you to ensure that it does the right thing.
- Currently the structure of the name tree is flat, it doesn't use Kids. But this can be changed if the need arise.

The following name trees can be filled with this method. Currently only the first three are activated. For the first, `EmbeddedFiles` there are two methods to add a value: `\pdfmanagement_add:nnn{Catalog/Names/EmbeddedFiles}{name}{reference}` and `\pdfmanagement_create:nnn{Catalog/Names/EmbeddedFiles}{name}`. This is intended, the second methods creates a name on the fly (with the prefix `l3ef`)

Catalog/Names/EmbeddedFiles	A name tree mapping name strings to file specifications for embedded files.
Catalog/Names/AP	A name tree mapping name strings to annotation appearance.
Catalog/Names/JavaScript	A name tree mapping name strings to documentlevel ECMAScript.
(inactive) Catalog/Names/Pages	A name tree mapping name strings to visible pages for use in page numbering.
(inactive) Catalog/Names/Templates	A name tree mapping name strings to invisible pages for use in page numbering.
(inactive) Catalog/Names/IDS	A name tree mapping digital identifiers to Web.Capture content.
(inactive) Catalog/Names/URLS	A name tree mapping name strings to documentlevel ECMAScript.
(inactive) Catalog/Names/Renditions	A name tree mapping name strings (which shall have Unicode).

2 `l3pdfmanagement` implementation

```

1  <@@=pdfmanagement>
2  <*header>
3  %
4  \ProvidesExplPackage{l3pdfmanagement}{2023-10-09}{0.96a}
5  {Management of core PDF dictionaries (LaTeX PDF management testphase bundle)}
6  </header>
```

2.1 Messages

```

7  <*package>
8  \msg_new:nnn  { pdfmanagement } { unknown-dict }
9    { The-PDF-management-resource-'#1'-is-unknown. }
10
11 \msg_new:nnn  { pdfmanagement } { empty-value }
12   { The-value-for-'#1'-is-empty-and-will-be-ignored }
13
14 \msg_new:nnn  { pdfmanagement } { no-removal }
15   { It-is-not-possible-to-remove-values-from-'#1'. }
16
17 \msg_new:nnn  { pdfmanagement } { no-show }
18   { It-is-not-possible-to-show-the-content-of-'#1'. }
19
20 \msg_new:nnn  { pdfmanagement } { name-exist }
21   { The-name-'#1'-has-already-been-used-for-name-tree-'#2'. }
22
23 \msg_new:nnn  { pdfmanagement } { show-dict }
24  {
25    The-PDF-resource-'#1'-
26    \tl_if_empty:nTF {#2}
27      { is-empty \\>- . }
28      { contains-the-pairs-(without-outer-braces): #2 . }
29  }
30 \msg_new:nnn  { pdfmanagement } { dict-already-defined }
31  {
32    The-path-'#1'-is-already-defined.
33  }
34 \msg_new:nnn  { pdfmanagement } { inactive }
```

```

35      {
36      The~PDF~resources~management~is~not~active\\
37      command~'#1'~ignored.
38  }

\l__pdfmanagement_tma_t1 Some temp variables
\l__pdfmanagement_tmb_t1
\l__pdfmanagement_tma_seq
39 \tl_new:N \l__pdfmanagement_tma_t1
40 \tl_new:N \l__pdfmanagement_tmb_t1
41 \seq_new:N \l__pdfmanagement_tma_seq

(End of definition for \l__pdfmanagement_tma_t1, \l__pdfmanagement_tmb_t1, and \l__pdfmanagement_tma_seq.)
```

\g__pdfmanagement_active_bool This boolean will control the activation of the management code. It is used in the hooks, and in some backend files. \DocumentMetadata should set it to true

```

42 \bool_new:N \g__pdfmanagement_active_bool

(End of definition for \g__pdfmanagement_active_bool.)
```

A user predicate to test if the management code is active

```

43 \prg_new_conditional:Npnn \__pdfmanagement_if_active: { p , T , F , TF }
44  {
45      \bool_if:NTF \g__pdfmanagement_active_bool
46      { \prg_return_true: }
47      { \prg_return_false: }
48  }
49 \prg_set_eq:conditional:NNn
50   \pdfmanagement_if_active: \__pdfmanagement_if_active: { p , T , F , TF }
51
52 \cs_set_eq:NN \IfPDFManagementActiveTF\pdfmanagement_if_active:TF
```

We use a hook, to collect value added before the backend is ready.

```

53 \hook_new:n {pdfmanagement/add}
54 \cs_new_protected:Npn \pdfmanagement_add:nnn #1 #2 #3
55  {
56      \__pdfmanagement_if_active:TF
57      {
58          \pdfdict_if_exist:nTF { g__pdf_Core/#1 }
59          {
60              \hook_gput_code:nnn
61              {pdfmanagement/add}
62              {pdfmanagement}
63              {
64                  \__pdfmanagement_handler_gput:nnn { #1 }{ #2 }{ #3 }
65              }
66          }
67          {
68              \msg_error:nnn{pdfmanagement}{unknown-dict}{#1}
69          }
70      }
71      {
72          \msg_warning:nnx {pdfmanagement}{inactive}
73          { \tl_to_str:n { \pdfmanagement_add:nnn } }
74      }
75  }
76
```

```

77 \cs_generate_variant:Nn \pdfmanagement_add:nnn {nnx,nxx,xxx}
78 \cs_set_eq:NN \PDFManagementAdd \pdfmanagement_add:xxx

```

2.2 Hooks – shipout and end of run code

Code is executed in three places: At shipout of every page, at shipout of the last page, at the end of the document (after the last clearpage). Due to backend differences the code in the three places (and the exact timing) can be different: pdflatex/lualatex can execute code after the last `\clearpage` which the dvi-based drivers have to add on a shipout page.

`...\\g_kernel_pdfmanagement_end_run_code_tl`

This variables contain the code run in the three places.

```

79 \tl_new:N \g_kernel_pdfmanagement_thispage_shipout_code_tl
80 \tl_new:N \g_kernel_pdfmanagement_lastpage_shipout_code_tl
81 \tl_new:N \g_kernel_pdfmanagement_end_run_code_tl

(End of definition for \g_kernel_pdfmanagement_thispage_shipout_code_tl      \g_kernel_pdfmanagement_-
lastpage_shipout_code_tl      \g_kernel_pdfmanagement_end_run_code_tl.)

82 \tl_gset:Nn \g_kernel_pdfmanagement_thispage_shipout_code_tl
83 {
84     \bool_if:NT \g_pdfmanagement_active_bool
85     {
86         \exp_args:NV \__pdf_backend_ThisPage_gpush:n      { \g_shipout_READONLY_int }
87         \exp_args:NV \__pdf_backend_PageResources_gpush:n { \g_shipout_READONLY_int }
88     }
89 }

90
91 \tl_gset:Nn \g_kernel_pdfmanagement_end_run_code_tl
92 {
93     \bool_if:NT \g_pdfmanagement_active_bool
94     {
95         \__pdf_backend_PageResources_obj_gpush:           %ExtGState etc
96         \__pdfmanagement_Pages_gpush:                   %pagesattr
97         \__pdfmanagement_Info_gpush:                  %pdfinfo
98         \__pdfmanagement_Catalog_gpush:
99     }
100 }

```

2.3 Naming convention

Currently the following names are used: All have internally additionally a `Core` before the slash, to hide the real name a bit.

<code>/Info</code>	%	<code>(\pdfinfo)</code>
<code>/Catalog</code>	%	<code>(\pdfcatalog)</code>
<code>/Catalog/AA</code>	%	
<code>/Catalog/AcroForm</code>		
<code>/Catalog/OCProperties</code>		
<code>/Catalog/OutputIntents</code>		
<code>/Catalog/AcroForm/DR</code>		
<code>/Catalog/AcroForm/DR/Font</code>		
<code>/Catalog/MarkInfo</code>		
<code>/Catalog/ViewerPreferences</code>		

```

/Pages % (\pagesattr)
/Page % (\pageattr)
/ThisPage % (\pageattr)
/backend_PageN/Resources/Properties % this is only internal.
/Page/Resources/ExtGState
/Page/Resources/ColorSpace
/Page/Resources/Pattern
/Page/Resources/Shading
/Page/Resources/Properties
/Xform/Resources/Properties

\__pdfmanagement_handler_gput:nnn is the main command to fill the dictionaries. In
simple cases it directly fill the property list, but if a handler exists this is called. It is
important to use it only in places where this make sense.

\__pdfmanagement_handler_gput:nnn
\__pdfmanagement_get:nnN
\__pdfmanagement_gremove:nn
\__pdfmanagement_show:n

101
102 %global
103 \cs_new_protected:Npn \__pdfmanagement_handler_gput:nnn #1 #2 #3 %#1 dict, #2 name, #3 value
104 {
105     \tl_if_empty:nTF { #3 }
106     {
107         \msg_none:nnn { pdfmanagement }{ empty-value }{ /#1/#2 }
108     }
109     {
110         \pdfdict_if_exist:nTF { g__pdf_Core/#1 }
111         {
112             \cs_if_exist:cTF
113                 { __pdfmanagement_handler/#1/?_gput:nn } %general, name independant handler
114                 { \use:c {__pdfmanagement_handler/#1/?_gput:nn} {#2} {#3} }
115             {
116                 \cs_if_exist:cTF
117                     { __pdfmanagement_handler/#1/#2_gput:n }
118                     { \use:c {__pdfmanagement_handler/#1/#2_gput:n} {#3} } %special handler
119             {
120                 \exp_args:Nnx
121                 \prop_gput:cnn
122                     { \__kernel_pdfdict_name:n { g__pdf_Core/#1 } }
123                     { \str_convert_pdfname:n { #2 } }
124                     { #3 }
125             }
126         }
127     }
128     {
129         \msg_error:nnn { pdfmanagement } { unknown-dict } { #1 }
130     }
131 }
132 }

133
134 \cs_generate_variant:Nn \__pdfmanagement_handler_gput:nnn {nxx}
135
136 \cs_new_protected:Npn \__pdfmanagement_get:nnN #1 #2 #3 %path,key,macro
137 {
138     \exp_args:Nnx

```

```

140     \prop_get:cnN
141     { \_kernel_pdfdict_name:n { g__pdf_Core/#1 } }
142     { \str_convert_pdfname:n {#2} } #3
143 }
144
145
146 \cs_new_protected:Npn \_pdfmanagement_handler_gremove:nn #1 #2 %path,key
147 {
148     \pdfdict_if_exist:nTF { g__pdf_Core/#1 }
149     {
150         \cs_if_exist:cTF
151         { __pdfmanagement_handler/#1/?_gremove:n } %general, name independant handler
152         { \use:c {__pdfmanagement_handler/#1/?_gremove:n} {#2} }
153         {
154             \cs_if_exist:cTF
155             { __pdfmanagement_handler/#1/#2_gremove: }
156             { \use:c {__pdfmanagement_handler/#1/#2_gremove:} } %special handler
157             {
158                 \exp_args:Nnx
159                 \prop_gremove:cn
160                 { \_kernel_pdfdict_name:n { g__pdf_Core/#1 } }
161                 { \str_convert_pdfname:n {#2} }
162             }
163         }
164     }
165     {
166         \msg_error:nnn { pdfmanagement } { unknown-dict } { #1 }
167     }
168 }
169
170 \cs_new_protected:Npn \_pdfmanagement_gremove:nn #1 #2 %path,key
171 {
172     \pdfdict_if_exist:nTF { g__pdf_Core/#1 }
173     {
174         \exp_args:Nnx
175         \prop_gremove:cn
176         { \_kernel_pdfdict_name:n { g__pdf_Core/#1 } }
177         { \str_convert_pdfname:n{#2} }
178     }
179     {
180         \msg_error:nnn { pdfmanagement } { unknown-dict } { #1 }
181     }
182 }
183
184
185 \cs_new_protected:Npn \_pdfmanagement_show:Nn #1#2
186 {
187     \cs_if_exist:cTF
188     { __pdfmanagement_handler/#2/?_show: } %general, name independant handler
189     { \use:c {__pdfmanagement_handler/#2/?_show:} }
190     {
191         \prop_if_exist:cTF { \_kernel_pdfdict_name:n { g__pdf_Core/#2 } }
192         {
193             #1

```

```

194     { pdfmanagement } { show-dict }
195     { \tl_to_str:n {#2} }
196     {
197         \prop_map_function:cN
198         {\_kernel_pdfdict_name:n { g__pdf_Core/#2 }}
199         \msg_show_item:nn
200     }
201     { } { }
202 }
203 {
204     #1 { pdfmanagement } { unknown-dict } {#2}{ }{ }{ }
205 }
206 }
207 }
208
209 \cs_new_protected:Npn \__pdfmanagement_show:n #1 %path
210 {
211     \prop_show:c { \_kernel_pdfdict_name:n { g__pdf_Core/#1 } }
212 }

(End of definition for \__pdfmanagement_handler_gput:nnn and others.)

213 \cs_new_protected:Npn \pdfmanagement_show:n #1
214 {
215     \__pdfmanagement_show:Nn \msg_show:nnxxxx {#1}
216 }

217 \cs_new_protected:Npn \pdfmanagement_remove:nn #1 #2
218 {
219     \pdfdict_if_exist:nTF { g__pdf_Core/#1 }
220     {
221         \__pdfmanagement_handler_gremove:nn { #1 }{ #2 }
222     }
223     {
224         \msg_error:nnn{pdfmanagement}{unknown-dict}{#1}
225     }
226 }

227 \cs_new_protected:Npn \pdfmanagement_get:nnN #1 #2 #3
228 {
229     \pdfdict_if_exist:nTF { g__pdf_Core/#1 }
230     {
231         \__pdfmanagement_get:nnN { #1 }{ #2 } #3
232     }
233     {
234         \msg_error:nnn{pdfmanagement}{unknown-dict}{#1}
235     }
236 }

```

2.4 The Info dictionary

Initialization of the dictionary:

```
237 \pdfdict_new:n { g__pdf_Core/Info}
```

__pdfmanagement_Info_gpush: is the command that outputs the info dictionary (currently in the end-of-run hooks).

```

238 % push to the register command / issue the special
239 \cs_new_protected:Npn \__pdfmanagement_Info_gpush:
240   {
241     \prop_map_function:cN
242       { \__kernel_pdfdict_name:n { g__pdf_Core/Info} }
243       \__pdf_backend_info_gput:nn
244     \prop_gclear:c { \__kernel_pdfdict_name:n { g__pdf_Core/Info} }
245   }

```

(End of definition for `__pdfmanagement_Info_gpush:..`)

2.5 The Pages dictionary code

At first the initialisation

```
246 \pdfdict_new:n { g__pdf_Core/Pages}
```

`__pdfmanagement_Pages_gpush:` This is the command that outputs the Pages dictionary. It is used at the end of the document in `\g__pdf_backend_end_run_tl`

```

247 % push to the register command / issue the special
248 \cs_new_protected:Npn \__pdfmanagement_Pages_gpush:
249   {
250     \pdfdict_if_empty:nF { g__pdf_Core/Pages}
251     {
252       \exp_args:Nx \__pdf_backend_Pages_primitive:n
253         {
254           \pdfdict_use:n { g__pdf_Core/Pages}
255         }
256     }
257   }
258

```

(End of definition for `__pdfmanagement_Pages_gpush:..`)

2.6 The Page and ThisPage dictionary

At first the initialisation.

```

259 \pdfdict_new:n { g__pdf_Core/Page }
260 \pdfdict_new:n { g__pdf_Core/ThisPage }
261
262 %handler for pdfmanagement
263 \cs_new_protected:cpx { __pdfmanagement_handler/Page/?_gput:nn } #1 #2
264   {
265     \__pdf_backend_Page_gput:nn { #1 }{ #2 }
266   }
267 % remove:
268 \cs_new_protected:cpx { __pdfmanagement_handler/Page/?_gremove:n } #1
269   {
270     \__pdf_backend_Page_gremove:n { #1 }
271   }
272
273 % handler for pdfmanagement
274 \cs_new_protected:cpx { __pdfmanagement_handler/ThisPage/?_gput:nn } #1 #2
275   {
276     \prop_gput:cnn { \__kernel_pdfdict_name:n { g__pdf_Core/ThisPage } }{ #1 } { #2 }

```

```

277     \bool_if:NT \g__pdfmanagement_active_bool
278     {
279         \__pdf_backend_ThisPage_gput:nn { #1 }{ #2 }
280     }
281 }
282
283 \cs_new_protected:cpn { __pdfmanagement_handler/ThisPage/?_gremove:n } #1
284 {
285     \msg_warning:nnn { pdfmanagement } { no-removal }{ThisPage}
286 }
287
288 \cs_new_protected:cpn { __pdfmanagement_handler/ThisPage/?_show: }
289 {
290     \msg_warning:nnn { pdfmanagement } { no-show }{ThisPage}
291 }
292

```

2.6.1 “Page/Resources”: ExtGState, ColorSpace, Shading, Pattern

```

293 \clist_const:Nn \c__pdfmanagement_PageResources_clist
294 {
295     ExtGState,
296     ColorSpace,
297     Pattern,
298     Shading,
299 }
300
301 \clist_map_inline:Nn \c__pdfmanagement_PageResources_clist
302 {
303     \pdfdict_new:n { g__pdf_Core/Page/Resources/#1}
304 }
305 %
306 % setter: #1 is the name of the resource
307 \cs_new_protected:cpn { __pdfmanagement_handler/Page/Resources/ExtGState/?_gput:nn } #1 #2
308 {
309     \__pdf_backend_PageResources_gput:nnn {ExtGState} { #1 }{ #2 }
310 }
311
312 \cs_new_protected:cpn { __pdfmanagement_handler/Page/Resources/ColorSpace/?_gput:nn } #1 #2
313 {
314     \__pdf_backend_PageResources_gput:nnn {ColorSpace} { #1 }{ #2 }
315 }
316
317 \cs_new_protected:cpn { __pdfmanagement_handler/Page/Resources/Shading/?_gput:nn } #1 #2
318 {
319     \__pdf_backend_PageResources_gput:nnn {Shading} { #1 }{ #2 }
320 }
321
322 \cs_new_protected:cpn { __pdfmanagement_handler/Page/Resources/Pattern/?_gput:nn } #1 #2
323 {
324     \__pdf_backend_PageResources_gput:nnn {Pattern} { #1 }{ #2 }
325 }

```

2.6.2 “Catalog”

The catalog has mixed entries: toplevel, subdictionaries, and entries which must build arrays.

This variables hold the list of the various types of entries. With it the various `_gput` commands are generated.

(*End of definition for \c__pdfmanagement_Catalog_toplevel_clist, \c__pdfmanagement_Catalog_sub_clist, and \c__pdfmanagement_Catalog_seq_clist.*)

Various commands to handle subentries and special cases. At first we set up a few lists of the various types.

```
326 \pdfdict_new:n { g__pdf_Core/Catalog}
327
328 \clist_const:Nn \c__pdfmanagement_Catalog_toplevel_clist
329 {
330   Collection,
331   DPartRoot,
332   Lang,
333   Legal,
334   Metadata,
335   NeedsRendering,
336   OCProperties/D,
337   OpenAction,
338   PageLabels,
339   PageLayout,
340   PageMode,
341   Perms,
342   PieceInfo,
343   SpiderInfo,
344   StructTreeRoot,
345   Threads,
346   URI,
347   Version
348 }
349
350 \clist_const:Nn \c__pdfmanagement_Catalog_sub_clist
351 {
352   AA,
353   AcroForm,
354   AcroForm/DR,
355   AcroForm/DR/Font,
356   MarkInfo,
357   ViewerPreferences,
358   OCProperties
359 }
360
361 \clist_map_inline:Nn \c__pdfmanagement_Catalog_sub_clist
362 {
363   \pdfdict_new:n { g__pdf_Core/Catalog/#1}
364 }
365
366
367 \clist_const:Nn \c__pdfmanagement_Catalog_seq_clist
```

```

368 {
369   AF,
370   OCProperties/OCGs,
371   OCProperties/Configs,
372   OutputIntents,
373   Requirements,
374   AcroForm/Fields,
375   AcroForm/CO
376 }
377

```

Names trees in Catalog/Names. We prepare the full list but activate only AP and JavaScript for now. /EmbeddedFiles has special code and so is not in the name list.

```

378 \clist_const:Nn \c__pdfmanagement_Catalog_nametree_clist
379 {
380   AP,
381   JavaScript,
382 % Pages,
383 % Templates,
384 % IDS,
385 % URLs,
386 % Renditions
387 }

```

now we create the handler. The entries in the seq-list store in a seq

```

388 \clist_map_inline:Nn \c__pdfmanagement_Catalog_seq_clist
389 {
390   \seq_new:c { g__pdfmanagement_/_Catalog/#1_seq } % new name later
391   \cs_new_protected:cpn { __pdfmanagement_handler/Catalog/#1_gput:n } ##1
392   {
393     \seq_gput_right:cn { g__pdfmanagement_/_Catalog/#1_seq } { ##1 }
394   }
395 }
396

```

OCProperties/D is special: it handles a default. This is done by adding to the left of the seq

```

397 \cs_new_protected:cpn { __pdfmanagement_handler/Catalog/OCProperties/D_gput:n } #1
398   {
399     \seq_gput_left:cn
400       { g__pdfmanagement_/_Catalog/OCProperties/Configs_seq }
401       { #1 }
402   }

```

The name tree keys store in a property and check for duplicates. This is done with an auxiliary.

```

403 \cs_new_protected:Npn \__pdfmanagement_nametree_add_aux:nnn #1 #2 #3
404   %#1 name tree, #2 sanitized name #3 value
405   {
406     \prop_get:coNTF
407       { __kernel_pdfdict_name:n { g__pdf_Core/Catalog/Names/#1 } }
408       { #2 }
409     \l__pdfmanagement_tmpb_tl
410     {
411       \msg_error:nnnn{pdfmanagement}{name-exist}{#2}{#1}

```

```

412     }
413     {
414         \prop_gput:con
415             { \__kernel_pdfdict_name:n { g__pdf_Core/Catalog/Names/#1 } }
416             { #2 }
417             { #3 }
418     }
419 }
```

This is the standard handler for most names trees:

```

420 \clist_map_inline:Nn \c__pdfmanagement_Catalog_nametree_clist
421 {
422     \pdfdict_new:n { g__pdf_Core/Catalog/Names/#1 }
423     \cs_new_protected:cpn { __pdfmanagement_handler/Catalog/Names/#1/?_gput:nn } ##1 ##2
424     {
425         \pdf_string_from_unicode:nnN {utf8/string}{##1}\l__pdfmanagement_tmpa_t1
426         \exp_args:Nno
427         \__pdfmanagement_nametree_add_aux:nnn {#1}{\l__pdfmanagement_tmpa_t1}{##2}
428     }
429 }
```

EmbeddedFiles is a bit special. For once there is special backend code needed by dvips. Beside this we also want the option to create the file name on the fly, so they are actually two access methods: \pdfmanagement_add:nnn{Catalog/Names/EmbeddedFiles}{name}{reference} and \pdfmanagement_add:nnn{Catalog/Names}{EmbeddedFiles}{reference}

```

430 \pdfdict_new:n { g__pdf_Core/Catalog/Names/EmbeddedFiles}
431 \cs_new_protected:cpn { __pdfmanagement_handler/Catalog/Names/EmbeddedFiles/?_gput:nn } #1 #2
432 {
433     \pdf_string_from_unicode:nnN {utf8/string}{#1}\l__pdfmanagement_tmpa_t1
434     \exp_args:Nno
435     \__pdfmanagement_nametree_add_aux:nnn
436         {EmbeddedFiles}{\l__pdfmanagement_tmpa_t1}{#2}
437     \exp_args:No
438     \__pdf_backend_NamesEmbeddedFiles_add:nn {\l__pdfmanagement_tmpa_t1}{#2}
439 }
```

(End of definition for __pdfmanagement_catalog_XX_gput:n.)

Building the catalog: Push order

__pdfmanagement_Catalog_gpush:

```

440 \cs_new_protected:Npn \__pdfmanagement_Catalog_gpush:
441     {
442         \use:c { __pdfmanagement_/_Catalog/AA_gpush: }
443         \use:c { __pdfmanagement_/_Catalog/AcroForm_gpush: }
444         \use:c { __pdfmanagement_/_Catalog/AF_gpush: }
445         \use:c { __pdfmanagement_/_Catalog/MarkInfo_gpush: }
446         \pdfmeta_standard_verify:nT {Catalog_no_OCProperties}
447         {
448             \use:c { __pdfmanagement_/_Catalog/OCProperties_gpush: }
449         }
450         \use:c { __pdfmanagement_/_Catalog/OutputIntents_gpush: }
451         \use:c { __pdfmanagement_/_Catalog/Requirements_gpush: }
452         \use:c { __pdfmanagement_/_Catalog/ViewerPreferences_gpush: }
453         % output the single values:
```

```

454 \prop_map_function:cN
455   { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog} }
456   \__pdf_backend_catalog_gput:nn
457 % output names tree:
458 \use:c{ __pdfmanagement_/_Catalog/Names_gpush:n } {EmbeddedFiles}
459 \clist_map_inline:Nn \c__pdfmanagement_Catalog_nametree_clist
460   {
461     \use:c{ __pdfmanagement_/_Catalog/Names_gpush:n } {##1}
462   }
463 }

(End of definition for \__pdfmanagement_Catalog_gpush:.)
```

Building catalog entries: AA

__pdfmanagement_/_Catalog/AA_gpush:

```

464 \cs_new_protected:cpn { __pdfmanagement_/_Catalog/AA_gpush: }
465   {
466     \prop_if_empty:cF
467     { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AA } }
468     {
469       \pdf_object_new:n { __pdfmanagement/Catalog/AA }
470       \pdf_object_write:nnx
471         { __pdfmanagement/Catalog/AA } { dict }
472         { \pdffdict_use:n { g__pdf_Core/Catalog/AA } }
473       \exp_args:Nnx
474         \__pdf_backend_catalog_gput:nn
475           {AA}
476           {
477             \__pdf_backend_object_ref:n { __pdfmanagement/Catalog/AA }
478           }
479     }
480   }

(End of definition for \__pdfmanagement_/_Catalog/AA_gpush:.)
```

Building catalog entries: AcroForm This is the most complicated case. The entries is build from /Catalog/AcroForm/Fields (array), /Catalog/AcroForm/CO (array), /Catalog/AcroForm/DR/Font (dict), /Catalog/AcroForm/DR (dict), /Catalog/AcroForm

__pdfmanagement_/_Catalog/AcroForm_gpush:

```

481 \cs_new_protected:cpn { __pdfmanagement_/_Catalog/AcroForm_gpush: }
482   {
483     \seq_if_empty:cF { g__pdfmanagement_/_Catalog/AcroForm/Fields_seq }
484     {
485       \pdf_object_new:n { __pdfmanagement/Catalog/AcroForm/Fields }
486       \pdf_object_write:nnx
487         { __pdfmanagement/Catalog/AcroForm/Fields } { array }
488         { \seq_use:cn { g__pdfmanagement_/_Catalog/AcroForm/Fields_seq } {~} }
489     \exp_args:Nnnx
490       \prop_gput:cnn %we have to use \prop here to avoid the handler ...
491         { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm } }
492         { Fields }
493         { \__pdf_backend_object_ref:n { __pdfmanagement/Catalog/AcroForm/Fields } }
```

```

494 }
495 \seq_if_empty:cF { g__pdfmanagement_/Catalog/AcroForm/C0_seq }
496 {
497   \pdf_object_new:n { __pdfmanagement/Catalog/AcroForm/C0 }
498   \pdf_object_write:nnx
499   { __pdfmanagement/Catalog/AcroForm/C0 } { array }
500   { \seq_use:cn { g__pdfmanagement_/Catalog/AcroForm/C0_seq } {~} }
501 \exp_args:Nnnx
502   \prop_gput:cnn %we have to use \prop here to avoid the handler ...
503   { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm } }
504   { C0 }
505   { \__pdf_backend_object_ref:n { __pdfmanagement/Catalog/AcroForm/C0 } }
506 }
507 \prop_if_empty:cF { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm/DR/Font} }
508 {
509   \pdf_object_new:n { __pdfmanagement/Catalog/AcroForm/DR/Font }
510   \pdf_object_write:nnx
511   { __pdfmanagement/Catalog/AcroForm/DR/Font } { dict }
512   { \pdffdict_use:n { g__pdf_Core/Catalog/AcroForm/DR/Font } }
513 \exp_args:Nnnx
514   \prop_gput:cnn %we have to use \prop here to avoid the handler ...
515   { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm/DR } }
516   { Font }
517   { \__pdf_backend_object_ref:n { __pdfmanagement/Catalog/AcroForm/DR/Font } }
518 }
519 \prop_if_empty:cF { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm/DR} }
520 {
521   \pdf_object_new:n { __pdfmanagement/Catalog/AcroForm/DR }
522   \pdf_object_write:nnx
523   { __pdfmanagement/Catalog/AcroForm/DR } { dict }
524   { \pdffdict_use:n { g__pdf_Core/Catalog/AcroForm/DR } }
525 \exp_args:Nnnx
526   \prop_gput:cnn %we have to use \prop here to avoid the handler ...
527   { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm } }
528   { DR }
529   { \__pdf_backend_object_ref:n { __pdfmanagement/Catalog/AcroForm/DR } }
530 }
531 \prop_if_empty:cF { \__kernel_pdffdict_name:n { g__pdf_Core/Catalog/AcroForm} }
532 {
533   \pdf_object_new:n { __pdfmanagement/Catalog/AcroForm }
534   \pdf_object_write:nnx
535   { __pdfmanagement/Catalog/AcroForm } { dict }
536   { \pdffdict_use:n { g__pdf_Core/Catalog/AcroForm } }
537 \exp_args:Nnnx
538   \__pdfmanagement_handler_gput:nnn
539   { Catalog }
540   { AcroForm }
541   { \__pdf_backend_object_ref:n { __pdfmanagement/Catalog/AcroForm } }
542 }
543 }
544

```

(End of definition for __pdfmanagement_/Catalog/AcroForm_gpush:.)

Building catalog entries: AF AF is an array.

_pdfmanagement_Catalog/AF_gpush:

```

545 \cs_new_protected:cpn { __pdfmanagement_/Catalog/AF_gpush: }
546   {
547     \seq_if_empty:cF
548     { g__pdfmanagement_/Catalog/AF_seq }
549     {
550       \pdf_object_new:n { __pdfmanagement/Catalog/AF }
551       \pdf_object_write:nnx
552         { __pdfmanagement/Catalog/AF } { array }
553         { \seq_use:cn { g__pdfmanagement_/Catalog/AF_seq } {~} }
554       \exp_args:Nnx
555         \__pdf_backend_catalog_gput:nn
556           {AF}
557           {
558             \__pdf_backend_object_ref:n {__pdfmanagement/Catalog/AF}
559           }
560         }
561     }

```

(End of definition for _pdfmanagement_Catalog/AF_gpush:.)

Building catalog entries: MarkInfo

_pdfmanagement/_Catalog/MarkInfo_gpush:

```

562 \cs_new_protected:cpn { __pdfmanagement_/Catalog/MarkInfo_gpush: }
563   {
564     \prop_if_empty:cF
565     { \__kernel_pdfdict_name:n { g__pdf_Core/Catalog/MarkInfo } }
566     {
567       \pdf_object_new:n { __pdfmanagement/Catalog/MarkInfo }
568       \pdf_object_write:nnx
569         { __pdfmanagement/Catalog/MarkInfo } { dict }
570         { \pdfdict_use:n { g__pdf_Core/Catalog/MarkInfo } }
571     \exp_args:Nnx
572       \__pdf_backend_catalog_gput:nn
573         {MarkInfo}
574         {
575           \__pdf_backend_object_ref:n {__pdfmanagement/Catalog/MarkInfo}
576         }
577       }
578     }

```

(End of definition for _pdfmanagement/_Catalog/MarkInfo_gpush:.)

Building catalog entries: OCProperties This is a dictionary with three entries:

- /OCGs (required) An array of indirect references, access needed for more than one package.
- /D (required) a dict (given as an object name) to the default configuration
- /Configs (optional) an array of indirect references to more configurations.

The /D entry is also a config, it is the first of the seq. The overall structure is nested: a dict with arrays.

pdfmanagement /Catalog/OCProperties_gpush:

```

579 % Catalog/OCProperties: OCGs + D is required
580 \cs_new_protected:cpn { __pdfmanagement_/Catalog/OCProperties_gpush: }
581 {
582   \int_compare:nNnt
583   {
584     ( \seq_count:c { g__pdfmanagement_/Catalog/OCProperties/OCGs_seq } )*
585     ( \seq_count:c { g__pdfmanagement_/Catalog/OCProperties/Configs_seq } )
586   }
587   >
588   { 0 }
589   {
590     \pdf_object_new:n { __pdfmanagement/Catalog/OCProperties }
591     \seq_gpop_left:cN { g__pdfmanagement_/Catalog/OCProperties/Configs_seq } \l__pdfmanag
592     \pdf_object_write:nnx { __pdfmanagement/Catalog/OCProperties } {dict}
593     {
594       /OCGs~[ \seq_use:cn { g__pdfmanagement_/Catalog/OCProperties/OCGs_seq } {~} ]
595       /D~\l__pdfmanagement_tmpa_t1~
596       \seq_if_empty:cF { g__pdfmanagement_/Catalog/OCProperties/Configs_seq }
597       {
598         /Configs~
599         [ \seq_use:cn { g__pdfmanagement_/Catalog/OCProperties/Configs_seq } {~} ]
600       }
601     }
602     \exp_args:Nnx
603     \__pdf_backend_catalog_gput:nn
604     { OCProperties }
605     { \__pdf_backend_object_ref:n {__pdfmanagement/Catalog/OCProperties} }
606   }
607 }
```

(End of definition for __pdfmanagement_/Catalog/OCProperties_gpush:.)

Building catalog entries: OutputIntents OutputIntents is an array.

pdfmanagement /Catalog/OutputIntents_gpush:

```

608 \cs_new_protected:cpn { __pdfmanagement_/Catalog/OutputIntents_gpush: }
609 {
610   \seq_if_empty:cF
611   { g__pdfmanagement_/Catalog/OutputIntents_seq }
612   {
613     \pdf_object_new:n { __pdfmanagement/Catalog/OutputIntents }
614     \pdf_object_write:nnx
615     { __pdfmanagement/Catalog/OutputIntents } { array }
616     { \seq_use:cn { g__pdfmanagement_/Catalog/OutputIntents_seq } {~} }
617   \exp_args:Nnx
618   \__pdf_backend_catalog_gput:nn
619   {OutputIntents}
620   {
621     \__pdf_backend_object_ref:n {__pdfmanagement/Catalog/OutputIntents}
622   }
```

```

623     }
624 }

```

(End of definition for __pdfmanagement__Catalog\OutputIntents_gpush:.)

Building catalog entries: Requirements Requirements is an array.

_pdfmanagement__Catalog\Requirements_gpush:

```

625 \cs_new_protected:cpn { __pdfmanagement\_\_Catalog\Requirements\_gpush: }
626 {
627   \seq_if_empty:cF
628   { g__pdfmanagement\_\_Catalog\Requirements_seq }
629   {
630     \pdf_object_new:n { __pdfmanagement\_\_Catalog\Requirements }
631     \pdf_object_write:nnx
632     { __pdfmanagement\_\_Catalog\Requirements } { array }
633     { \seq_use:cn { g__pdfmanagement\_\_Catalog\Requirements_seq } {~} }
634     \exp_args:Nnx
635       \__pdf_backend_catalog_gput:nn
636       { Requirements }
637       {
638         \__pdf_backend_object_ref:n { __pdfmanagement\_\_Catalog\Requirements }
639       }
640   }
641 }

```

(End of definition for __pdfmanagement__Catalog\Requirements_gpush:.)

Building catalog entries: ViewerPreferences

anagement__Catalog\ViewerPreferences_gpush:

```

642 \cs_new_protected:cpn { __pdfmanagement\_\_Catalog\ViewerPreferences\_gpush: }
643 {
644   \prop_if_empty:cF
645   { \__kernel_pdfdict_name:n { g__pdf_Core\_\_Catalog\ViewerPreferences } }
646   {
647     \pdf_object_new:n { __pdfmanagement\_\_Catalog\ViewerPreferences }
648     \pdf_object_write:nnx
649     { __pdfmanagement\_\_Catalog\ViewerPreferences } { dict }
650     { \pdfdict_use:n { g__pdf_Core\_\_Catalog\ViewerPreferences } }
651     \exp_args:Nnx
652       \__pdf_backend_catalog_gput:nn
653       { ViewerPreferences }
654       {
655         \__pdf_backend_object_ref:n { __pdfmanagement\_\_Catalog\ViewerPreferences }
656       }
657   }
658 }

```

(End of definition for __pdfmanagement__Catalog\ViewerPreferences_gpush:.)

Building catalog entries: Names/EmbeddedFiles

\g_pdfmanagement_EMBEDDEDFILES_int

We want to create names for files on the fly. For this we use an int.

659 \int_new:N \g_pdfmanagement_EMBEDDEDFILES_int

(End of definition for \g_pdfmanagement_EMBEDDEDFILES_int.)

_pdfmanagement_EMBEDDEDFILES_name:

We use the prefix l3ef, and pad numbers below 9999.

660 \cs_new:Npn _pdfmanagement_EMBEDDEDFILES_name:

{

662 (

663 13ef

664 \int_compare:nNnT {\g_pdfmanagement_EMBEDDEDFILES_int} < {10}

665 {0}

666 \int_compare:nNnT {\g_pdfmanagement_EMBEDDEDFILES_int} < {100}

667 {0}

668 \int_compare:nNnT {\g_pdfmanagement_EMBEDDEDFILES_int} < {1000}

669 {0}

670 \int_use:N \g_pdfmanagement_EMBEDDEDFILES_int

)

671 }

672 }

(End of definition for _pdfmanagement_EMBEDDEDFILES_name:.)

_handler/Catalog/Names/EmbeddedFiles_gput:n

EmbeddedFiles is an array and needs a special handler to add values.

673 \pdfdict_new:n { g_pdf_Core/Catalog/Names }

674

675 \cs_new_protected:cpn { __pdfmanagement_handler/Catalog/Names/EmbeddedFiles_gput:n } #1

{

677 \int_gincr:N \g_pdfmanagement_EMBEDDEDFILES_int

678 \exp_args:Nnx

679 \prop_gput:cnn

680 { \kernel_pdfdict_name:n { g_pdf_Core/Catalog/Names/EmbeddedFiles } }

681 { __pdfmanagement_EMBEDDEDFILES_name: }

682 { #1 }

683 \exp_args:Nx

684 __pdf_backend_NamesEmbeddedFiles_add:nn { __pdfmanagement_EMBEDDEDFILES_name: } { #1 }

}

(End of definition for __pdfmanagement_handler/Catalog/Names/EmbeddedFiles_gput:n.)

This pushes out the other names trees (but not with dvips). TODO: currently it simply write in the root of the name tree. That is the fastest. If they get longer we perhaps need to build something with Kids and Limits.

_pdfmanagement_Catalog/Names/?_gpush:

686 \cs_new_protected:cpn { __pdfmanagement_Catalog/Names_gpush:n } #1 %#1 name of name tree

{

688 \pdfdict_if_empty:nF { g_pdf_Core/Catalog/Names/#1 }

{

690 \seq_clear:N \l__pdfmanagement_tmpa_seq

691 \prop_map_inline:cn

{ \kernel_pdfdict_name:n { g_pdf_Core/Catalog/Names/#1 } }

693 { \seq_put_right:Nn \l__pdfmanagement_tmpa_seq {##1-##2}}

694 \seq_sort:Nn \l__pdfmanagement_tmpa_seq

{

```

696          \str_compare:nNnTF {##1} > {##2}
697              { \sort_return_swapped: }
698              { \sort_return_same: }
699      }
700  \exp_args:Nnx \__pdf_backend_Names_gpush:nn
701      {#1}
702      {
703          \seq_use:Nn \l__pdfmanagement_tmpa_seq {~}
704      }
705  }
706 }

(End of definition for \__pdfmanagement_/Catalog/Names/?_gpush:..)

```

_pdfmanagement_handler/Catalog/?_show: A handler to show the catalog.

```

707 \cs_new_protected:cpn \__pdfmanagement_handler/Catalog/?_show:
708 {
709     \iow_term:x
710     {
711         \iow_newline:
712         The~Catalog~contains~in~the~top~level~the~single~value~entries
713         \prop_map_function:cN
714             {\__kernel_pfdict_name:n { g__pdf_Core/Catalog }}
715         \msg_show_item:nn
716     }
717     \clist_map_inline:Nn \c__pdfmanagement_Catalog_seq_clist
718     {
719         \seq_if_empty:cF { g__pdfmanagement_/Catalog/##1_seq }
720         {
721             \iow_term:x
722             {
723                 The~'##1'~array~contains~the~entries
724                 \seq_map_function:cN { g__pdfmanagement_/Catalog/##1_seq } \msg_show_item:n
725             }
726         }
727     }
728     \clist_map_inline:Nn \c__pdfmanagement_Catalog_sub_clist
729     {
730         \prop_if_empty:cF { \__kernel_pfdict_name:n { g__pdf_Core/Catalog/##1 } }
731         {
732             \iow_term:x
733             {
734                 The~Catalog~subdirectory~'##1'~contains~the~single~value~entries
735                 \prop_map_function:cN
736                     {\__kernel_pfdict_name:n { g__pdf_Core/Catalog/##1 }}
737                 \msg_show_item:nn
738             }
739         }
740     }
741     \tl_show:x {\tl_to_str:n{\pdfmanagement_show:n{Catalog}}}
742 }

```

(End of definition for __pdfmanagement_handler/Catalog/?_show:..)

2.7 xform / Properties

```
743 \pdfdict_new:n { g__pdf_Core/Xform/Resources/Properties}
744 
```

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
\\\hspace{1pt} 27, 36
B	
bool commands:	
\bool_if:NTF	45, 84, 93, 277
\bool_new:N	42
C	
\clearpage	12
clist commands:	
\clist_const:Nn	293, 328, 350, 367, 378
\clist_map_inline:Nn 301, 361, 388, 420, 459, 717, 728
cs commands:	
\cs_generate_variant:Nn	77, 135
\cs_if_exist:NTF	112, 116, 150, 154, 187
\cs_new:Npn	660
\cs_new_protected:Npn	54, 103, 137, 146, 170, 185, 209, 213, 217, 227, 239, 248, 263, 268, 274, 283, 288, 307, 312, 317, 322, 391, 397, 403, 423, 431, 440, 464, 481, 545, 562, 580, 608, 625, 642, 675, 686, 707
\cs_set_eq:NN	52, 78
D	
\DocumentMetadata	11
E	
exp commands:	
\exp_args:Nnnx	489, 501, 513, 525, 537
\exp_args:Nno	426, 434
\exp_args:Nnx	120, 139, 158, 174, 473, 554, 571, 602, 617, 634, 651, 678, 700
\exp_args:No	437
\exp_args:NV	86, 87
\exp_args:Nx	252, 683
H	
hook commands:	
\hook_gput_code:nnn	60
I	
\IfPDFManagementActiveTF	2, 52
int commands:	
\int_compare:nNnTF	582, 664, 666, 668
\int_gincr:N	677
\int_new:N	659
\int_use:N	670
iow commands:	
\iow_newline:	711
\iow_term:n	709, 721, 732
K	
kernel internal commands:	
_kernel_pdfdict_name:n 122, 141, 160, 176, 191, 198, 211, 242, 244, 276, 407, 415, 455, 467, 491, 503, 507, 515, 519, 527, 531, 565, 645, 680, 692, 714, 730, 736
\g_kernel_pdfmanagement_end_-run_code_tl	81, 91
\g_kernel_pdfmanagement_-lastpage_shipout_code_tl	80
\g_kernel_pdfmanagement_-thispage_shipout_code_tl	79, 82
\g_kernel_pdfmanagement_-thispage_shipout_code_-tl\uuuuuu\g_kernel_pdfmanagement_-lastpage_shipout_code_-tl\uuuuuu\g_kernel_pdfmanagement_-end_run_code_tl	79
M	
msg commands:	
\msg_error:nnn 68, 129, 166, 180, 224, 234
\msg_error:nnnn	411
\msg_new:nnn	8, 11, 14, 17, 20, 23, 30, 34
\msg_none:nnn	107
\msg_show:nnnnnn	215
\msg_show_item:n	724

\msg_show_item:nn	199, 715, 737
\msg_warning:nnn	72, 285, 290
N	
\newpage	5
P	
pdf commands:	
\pdf_object_new:n	469, 485, 497, 509, 521, 533, 550, 567, 590, 613, 630, 647
\pdf_object_write:nnn	470, 486, 498, 510, 522, 534, 551, 568, 592, 614, 631, 648
\pdf_string_from_unicode:nnN	425, 433
pdf internal commands:	
__pdf_backend_catalog_gput:nn	456, 474, 555, 572, 603, 618, 635, 652
\g__pdf_backend_end_run_tl	16
__pdf_backend_info_gput:nn	243
__pdf_backend_Names_gpush:nn	700
__pdf_backend_NamesEmbeddedFiles_- add:nn	438, 684
__pdf_backend_object_ref:n	477, 493, 505, 517, 529, 541, 558, 575, 605, 621, 638, 655
__pdf_backend_Page_gput:nn	265
__pdf_backend_Page_gremove:n	270
__pdf_backend_PageResources_- gpush:n	87
__pdf_backend_PageResources_- gput:nnn	309, 314, 319, 324
__pdf_backend_PageResources_- obj_gpush:	95
__pdf_backend_Pages_primitive:n	252
__pdf_backend_ThisPage_gpush:n	86
__pdf_backend_ThisPage_gput:nn	279
\pdfcatalog	1, 2
pdfdict commands:	
\pdfdict_if_empty:nTF	250, 688
\pdfdict_if_exist:nTF	58, 110, 148, 172, 219, 229
\pdfdict_new:n	237, 246, 259, 260, 303, 326, 363, 422, 430, 673, 743
\pdfdict_use:n	254, 472, 512, 524, 536, 570, 650
\pdfinfo	1, 2
pdfmanagement commands:	
pdfmanagement:Info	4
pdfmanagement:Page	5
pdfmanagement:Page/Resources/ColorSpace	6
pdfmanagement:Page/Resources/ExtGState	6
pdfmanagement:Page/Resources/Pattern	6
pdfmanagement:Page/Resources/Shading	6
pdfmanagement:Pages	5
pdfmanagement:ThisPage	5
\pdfmanagement_add:nnn	3–6, 54, 73, 77, 78
\pdfmanagement_get:nnN	227
\pdfmanagement_if_active:	50
\pdfmanagement_if_active:TF	2, 52
\pdfmanagement_if_active_p:	2
\pdfmanagement_remove:nn	3, 5, 217
\pdfmanagement_show:n	3, 5, 213, 741
pdfmanagement internal commands:	
__pdfmanagement_Catalog/AA_- gpush:	464
__pdfmanagement_Catalog/AcroForm_- gpush:	481
__pdfmanagement_Catalog/AF_- gpush:	545
__pdfmanagement_Catalog/MarkInfo_- gpush:	562
__pdfmanagement_Catalog/Names/?_- gpush:	686
__pdfmanagement_Catalog/OCPProperties_- gpush:	579
__pdfmanagement_Catalog/OutputIntents_- gpush:	608
__pdfmanagement_Catalog/Requirements_- gpush:	625
__pdfmanagement_Catalog/ViewerPreferences_- gpush:	642
\g__pdfmanagement_active_bool	42, 45, 84, 93, 277
__pdfmanagement_Catalog_gpush:	98, 440, 440
\c__pdfmanagement_Catalog_- nametree_clist	378, 420, 459
\c__pdfmanagement_Catalog_seq_- clist	326, 367, 388, 717
\c__pdfmanagement_Catalog_sub_- clist	326, 350, 361, 728
\c__pdfmanagement_Catalog_- toplevel_clist	326, 328
__pdfmanagement_catalog_XX_- gput:n	326
\g__pdfmanagement_EMBEDDEDFILES_- int	659, 664, 666, 668, 670, 677
__pdfmanagement_EMBEDDEDFILES_- name:	660, 660, 681, 684
__pdfmanagement_get:nnN	101, 137, 231
__pdfmanagement_gremove:nn	101, 170

```

__pdfmanagement_handler/Catalog/?_-          \prop_if_exist:NTF ..... 191
    show: ..... 707          \prop_map_function:NN .....
\__pdfmanagement_handler/Catalog/Names/EmbeddedFiles_-... 197, 241, 454, 713, 735
    gput:n ..... 673          \prop_map_inline:Nn ..... 691
\__pdfmanagement_handler_-                  \prop_show:N ..... 211
    gput:nnn . 13, 64, 101, 103, 135, 538  \ProvidesExplPackage ..... 4
\__pdfmanagement_handler_-
    gremove:nn ..... 146, 221
\__pdfmanagement_if_active: . 43, 50
\__pdfmanagement_if_active:TF ... 56
\__pdfmanagement_Info_gpush: ...
    ..... 15, 97, 238, 239
\__pdfmanagement_nametree_add_-
    aux:nnn ..... 403, 427, 435
\c__pdfmanagement_PageResources_-
    clist ..... 293, 301
\__pdfmanagement_Pages_gpush: ...
    ..... 96, 247, 248
\__pdfmanagement_show:n .... 101, 209
\__pdfmanagement_show:Nn ... 185, 215
\l__pdfmanagement_tmqa_seq ...
    ..... 39, 690, 693, 694, 703
\l__pdfmanagement_tmqa_t1 ...
    ..... 39, 425, 427, 433, 436, 438, 591, 595
\l__pdfmanagement_tmrb_t1 ... 39, 409
\PDFManagementAdd ..... 3, 78
pdfmeta commands:
    \pdfmeta_standard_verify:nTF .. 446
\pdfpageattr ..... 1, 2, 5
\pdfpageheight ..... 5
\pdfpageresources ..... 1, 2, 6
\pdfpagesattr ..... 1, 2, 5
prg commands:
    \prg_new_conditional:Npnn ..... 43
    \prg_return_false: ..... 47
    \prg_return_true: ..... 46
    \prg_set_eq_conditional:NNn ... 49
\prop ..... 490, 502, 514, 526
prop commands:
    \prop_gclear:N ..... 244
    \prop_get:NnN ..... 140
    \prop_get:NnNTF ..... 406
    \prop_gput:Nnn ...
        ..... 121, 276, 414, 490, 502, 514, 526, 679
    \prop_gremove:Nn ..... 159, 175
    \prop_if_empty:NTF ...
        ..... 466, 507, 519, 531, 564, 644, 730
                                \prop_if_exist:NTF ..... 191
                                \prop_map_function:NN .....
                                \prop_map_inline:Nn ..... 691
                                \prop_show:N ..... 211
                                \ProvidesExplPackage ..... 4

```

S

seq commands:

```

\seq_clear:N ..... 690
\seq_count:N ..... 584, 585
\seq_gpop_left:NN ..... 591
\seq_gput_left:Nn ..... 399
\seq_gput_right:Nn ..... 393
\seq_if_empty:NTF ...
    ..... 483, 495, 547, 596, 610, 627, 719
\seq_map_function:NN ..... 724
\seq_new:N ..... 41, 390
\seq_put_right:Nn ..... 693
\seq_sort:Nn ..... 694
\seq_use:Nn ...
    ..... 488, 500, 553, 594, 599, 616, 633, 703

```

shipout commands:

```

\g_shipout_READONLY_int ..... 86, 87

```

sort commands:

```

\sort_return_same: ..... 698
\sort_return_swapped: ..... 697
\special ..... 1

```

str commands:

```

\str_compare:nNnTF ..... 696
\str_convert_pdfname:n ...
    ..... 3, 4, 123, 142, 161, 177

```

T

tl commands:

```

\tl_gset:Nn ..... 82, 91
\tl_if_empty:nTF ..... 26, 105
\tl_new:N ..... 39, 40, 79, 80, 81
\tl_show:n ..... 741
\tl_to_str:n ..... 73, 195, 741

```

U

use commands:

```

\use:N ..... 114, 118, 152, 156, 189, 442, 443,
    444, 445, 448, 450, 451, 452, 458, 461

```