
jupyter_core Documentation

Release 4.1.0

Jupyter Development Team

Mar 12, 2017

CONTENTS

1	Paths for Jupyter files	3
1.1	Specific directories	3
1.2	Search paths	3
2	Changes in jupyter-core	5
2.1	4.3	5
2.2	4.2	5
2.3	4.1	5
2.4	4.0	6
3	Indices and tables	7
	Python Module Index	9

This documentation only describes the public API in the `jupyter_core` package. For overview information about using Jupyter, see the [main Jupyter docs](#).

Contents:

PATHS FOR JUPYTER FILES

1.1 Specific directories

`jupyter_core.paths.jupyter_config_dir()`
Get the Jupyter config directory for this platform and user.
Returns JUPYTER_CONFIG_DIR if defined, else ~/.jupyter

`jupyter_core.paths.jupyter_data_dir()`
Get the config directory for Jupyter data files.
These are non-transient, non-configuration files.
Returns JUPYTER_DATA_DIR if defined, else a platform-appropriate path.

`jupyter_core.paths.jupyter_runtime_dir()`
Return the runtime dir for transient jupyter files.
Returns JUPYTER_RUNTIME_DIR if defined.
Respects XDG_RUNTIME_DIR on non-OS X, non-Windows, falls back on data_dir/runtime otherwise.

1.2 Search paths

`jupyter_core.paths.jupyter_config_path()`
Return the search path for Jupyter config files as a list.

`jupyter_core.paths.jupyter_path(*subdirs)`
Return a list of directories to search for data files
JUPYTER_PATH environment variable has highest priority.
If *subdirs are given, that subdirectory will be added to each element.
Examples:

```
>>> jupyter_path()
['~/.local/jupyter', '/usr/local/share/jupyter']
>>> jupyter_path('kernels')
['~/.local/jupyter/kernels', '/usr/local/share/jupyter/kernels']
```


CHANGES IN JUPYTER-CORE

2.1 4.3

2.1.1 4.3.0

on [GitHub](#)

- Add `JUPYTER_NO_CONFIG` environment variable for disabling all Jupyter configuration.
- More detailed error message when failing to launch subcommands.

2.2 4.2

2.2.1 4.2.1

on [GitHub](#)

- Fix error message on Windows when subcommand not found.
- Correctly display PATH in `jupyter troubleshoot` on Windows.

2.2.2 4.2.0

on [GitHub](#)

- Make `jupyter` directory top priority in search path for subcommands, so that `jupyter-subcommand` next to `jupyter` will always be picked if present.
- Avoid using `shell=True` for subcommand dispatch on Windows.

2.3 4.1

2.3.1 4.1.1

on [GitHub](#)

- Include symlink directory and real location on subcommand PATH when `jupyter` is a symlink.

2.3.2 4.1.0

on [GitHub](#)

- Add `jupyter.py` module, so that `python -m jupyter` always works.
- Add prototype `jupyter troubleshoot` command for displaying environment info.
- Ensure directory containing `jupyter` executable is included when dispatching subcommands.
- Unicode fixes for Legacy Python.

2.4 4.0

2.4.1 4.0.6

on [GitHub](#)

- fix typo preventing migration when `custom.css` is missing

2.4.2 4.0.5

on [GitHub](#)

- fix subcommands on Windows (yes, again)
- fix migration when `custom.js/css` are not present

2.4.3 4.0.4

on [GitHub](#)

- fix subcommands on Windows (again)
- ensure `jupyter --version` outputs to stdout

2.4.4 4.0.3

on [GitHub](#)

- `setuptools` fixes needed to run on Windows

2.4.5 4.0.2

on [GitHub](#)

- fixes for `jupyter-migrate`

2.4.6 4.0.1

on [GitHub](#)

This is the first release of the `jupyter-core` package.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

j

`jupyter_core.paths`, 3