

Package ‘cforward’

October 12, 2022

Title Forward Selection using Concordance/C-Index

Version 0.1.0

Description Performs forward model selection, using the C-index/concordance in survival analysis models.

License GPL-3

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

Imports survival, dplyr, stats, magrittr, tibble

URL <https://github.com/muschellij2/cforward>

BugReports <https://github.com/muschellij2/cforward/issues>

Depends R (>= 2.10)

Suggests testthat

NeedsCompilation no

Author John Muschelli [aut, cre] (<<https://orcid.org/0000-0001-6469-1750>>),
Andrew Leroux [aut]

Maintainer John Muschelli <muschellij2@gmail.com>

Repository CRAN

Date/Publication 2021-03-29 14:20:08 UTC

R topics documented:

cforward	2
estimate_concordance	4
nhanes_example	5

Index	6
--------------	----------

`cforward`*Forward Selection Based on C-Index/Concordance*

Description

Forward Selection Based on C-Index/Concordance

Usage

```
cforward(  
  data,  
  event_time = "event_time_years",  
  event_status = "mortstat",  
  weight_column = "WTMEC4YR_norm",  
  variables = NULL,  
  included_variables = NULL,  
  n_folds = 10,  
  seed = 1989,  
  max_model_size = 50,  
  c_threshold = NULL,  
  verbose = TRUE,  
  cfit_args = list(),  
  save_memory = FALSE,  
  ...  
)
```

```
cforward_one(  
  data,  
  event_time = "event_time_years",  
  event_status = "mortstat",  
  weight_column = "WTMEC4YR_norm",  
  variables,  
  included_variables = NULL,  
  verbose = TRUE,  
  cfit_args = list(),  
  save_memory = FALSE,  
  ...  
)
```

```
make_folds(data, event_status = "mortstat", n_folds = 10, verbose = TRUE)
```

Arguments

<code>data</code>	A data set to perform model selection and cross-validation.
<code>event_time</code>	Character vector of length 1 with event times, passed to Surv
<code>event_status</code>	Character vector of length 1 with event status, passed to Surv

<code>weight_column</code>	Character vector of length 1 with weights for model. If no weights are available, set to NULL
<code>variables</code>	Character vector of variables to perform selection. Must be in data.
<code>included_variables</code>	Character vector of variables forced to have in the model. Must be in data
<code>n_folds</code>	Number of folds for Cross-validation. If you want to run on the full data, set to 1
<code>seed</code>	Seed set before folds are created.
<code>max_model_size</code>	maximum number of variables in the model. Selection will stop if reached. Note, this does not correspond to the number of coefficients, due to categorical variables.
<code>c_threshold</code>	threshold for concordance. If the difference in the best concordance and this one does not reach a certain threshold, break.
<code>verbose</code>	print diagnostic messages
<code>cfit_args</code>	Arguments passed to <code>concordancefit</code> . If strata is to be passed, set <code>strata_column</code> in this list.
<code>save_memory</code>	save only a minimal amount of information, discard the fitted models
<code>...</code>	Additional arguments to pass to <code>coxph</code>

Value

A list of lists, with elements of:

full_concordance Concordance when fit on the full data

models Cox model from full data set fit, stripped of large memory elements

cv_concordance Cross-validated Concordance

included_variables Variables included in the model, other than those being selection upon

Examples

```
variables = c("gender",
             "age_years_interview", "education_adult")

res = cforward(nhanes_example,
              event_time = "event_time_years",
              event_status = "mortstat",
              weight_column = "WTMEC4YR_norm",
              variables = variables,
              included_variables = NULL,
              n_folds = 5,
              c_threshold = 0.02,
              seed = 1989,
              max_model_size = 50,
              verbose = TRUE)
conc = sapply(res, `[[`, "best_concordance")
```

```

res = cforward(nhanes_example,
               event_time = "event_time_years",
               event_status = "mortstat",
               weight_column = "WTMEC4YR_norm",
               variables = variables,
               included_variables = NULL,
               n_folds = 5,
               seed = 1989,
               max_model_size = 50,
               verbose = TRUE)
conc = sapply(res, `[[`, "best_concordance")
threshold = 0.01
included_variables = names(conc)[c(1, diff(conc)) > threshold]

new_variables = c("diabetes", "stroke")
second_level = cforward(nhanes_example,
                       event_time = "event_time_years",
                       event_status = "mortstat",
                       weight_column = "WTMEC4YR_norm",
                       variables = new_variables,
                       included_variables = included_variables,
                       n_folds = 5,
                       seed = 1989,
                       max_model_size = 50,
                       verbose = TRUE)
second_conc = sapply(second_level, `[[`, "best_concordance")
result = second_level[[which.max(second_conc)]]
final_model = result$models[[which.max(result$cv_concordance)]]

```

estimate_concordance *Estimate Out-of-Sample Concordance*

Description

Estimate Out-of-Sample Concordance

Usage

```

estimate_concordance(
  train,
  test = train,
  event_time = "event_time_years",
  event_status = "mortstat",
  weight_column = "WTMEC4YR_norm",
  all_variables = NULL,
  cfit_args = list(),
  ...
)

```

Arguments

<code>train</code>	A data set to perform model training.
<code>test</code>	A data set to estimate concordance, from fit model with <code>train</code> . Set to <code>train</code> if estimating on the same data
<code>event_time</code>	Character vector of length 1 with event times, passed to Surv
<code>event_status</code>	Character vector of length 1 with event status, passed to Surv
<code>weight_column</code>	Character vector of length 1 with weights for model. If no weights are available, set to <code>NULL</code>
<code>all_variables</code>	Character vector of variables to put in the model. All must be in data.
<code>cfit_args</code>	Arguments passed to concordancefit . If <code>strata</code> is to be passed, set <code>strata_column</code> in this list.
<code>...</code>	Additional arguments to pass to coxph

Value

A list of concordance and the model fit with the training data

<code>nhanes_example</code>	<i>Example Data from National Health and Nutrition Examination Survey ('NHANES')</i>
-----------------------------	--

Description

Example Data from National Health and Nutrition Examination Survey ('NHANES')

Usage

```
nhanes_example
```

Format

A data.frame with 7 columns, which are:

SEQN ID of participant

mortstat mortality status, 1-died, 0 - censored

event_time_years time observed

WTMEC4YR_norm weights normalized for survey

gender gender

age_years_interview age in years at interview

education_adult educational status

Index

* datasets

nhanes_example, 5

cforward, 2

cforward_one (cforward), 2

concordancefit, 3, 5

coxph, 3, 5

estimate_concordance, 4

make_folds (cforward), 2

nhanes_example, 5

Surv, 2, 5